

## Savitch's Theorem - 2

The space efficient algorithm for reachability used on the configuration graph of a nondeterministic machine shows:

$$\text{NSPACE}(f(n)) \subseteq \text{SPACE}(f(n)^2)$$

for  $f(n) \geq \log n$ .

This yields

$$\text{PSPACE} = \text{NSPACE} = \text{co-NPSPACE}.$$

## Complementation

A still more clever algorithm for [Reachability](#) has been used to show that nondeterministic space classes are closed under complementation:

If  $f(n) \geq \log n$ , then

$$\text{NSPACE}(f(n)) = \text{co-NSPACE}(f(n))$$

In particular

$$\text{NL} = \text{co-NL}.$$

## Complexity Classes

We have established the following inclusions among complexity classes:

$$L \subseteq NL \subseteq P \subseteq NP \subseteq PSPACE \subseteq EXP$$

Showing that a problem is **NP**-complete or **PSPACE**-complete, we often say that we have proved it intractable.

While this is not strictly correct, a proof of completeness for these classes does tell us that the problem is structurally difficult.

Similarly, we say that **PSPACE**-complete problems are harder than **NP**-complete ones, even if the running time is not higher.

## Provable Intractability

Our aim now is to show that there are languages (*or, equivalently, decision problems*) that we can prove are not in  $P$ .

This is done by showing that, for every *reasonable* function  $f$ , there is a language that is not in  $\text{TIME}(f(n))$ .

The proof is based on the diagonal method, as in the proof of the undecidability of the halting problem.

## Constructible Functions

A complexity class such as  $\text{TIME}(f(n))$  can be very unnatural, if  $f(n)$  is.

We restrict our bounding functions  $f(n)$  to be proper functions:

### Definition

A function  $f : \mathbb{N} \rightarrow \mathbb{N}$  is *constructible* if:

- $f$  is non-decreasing, i.e.  $f(n+1) \geq f(n)$  for all  $n$ ; and
- there is a deterministic machine  $M$  which, on any input of length  $n$ , replaces the input with the string  $0^{f(n)}$ , and  $M$  runs in time  $O(n + f(n))$  and uses  $O(f(n))$  work space.

## Examples

All of the following functions are constructible:

- $\lceil \log n \rceil$ ;
- $n^2$ ;
- $n$ ;
- $2^n$ .

If  $f$  and  $g$  are constructible functions, then so are  $f + g$ ,  $f \cdot g$ ,  $2^f$  and  $f(g)$  (this last, provided that  $f(n) > n$ ).

## Using Constructible Functions

Recall  $\text{NTIME}(f(n))$  is defined as the class of those languages  $L$  accepted by a *nondeterministic* Turing machine  $M$ , such that for every  $x \in L$ , there is an accepting computation of  $M$  on  $x$  of length at most  $O(f(n))$ .

If  $f$  is a constructible function then any language in  $\text{NTIME}(f(n))$  is accepted by a machine for which all computations are of length at most  $O(f(n))$ .

Also, given a Turing machine  $M$  and a constructible function  $f$ , we can define a machine that simulates  $M$  for  $f(n)$  steps.

## Inclusions

The inclusions we proved between complexity classes:

- $\text{NTIME}(f(n)) \subseteq \text{SPACE}(f(n))$ ;
- $\text{NSPACE}(f(n)) \subseteq \text{TIME}(k^{\log n} + f(n))$ ;
- $\text{NSPACE}(f(n)) \subseteq \text{SPACE}(f(n)^2)$

really only work for *constructible* functions  $f$ .

The inclusions are established by showing that a deterministic machine can simulate a nondeterministic machine  $M$  for  $f(n)$  steps.

For this, we have to be able to compute  $f$  within the required bounds.



## Time Hierarchy Theorem

For any constructible function  $f$ , with  $f(n) \geq n$ , define the  $f$ -bounded *halting language* to be:

$$H_f = \{[M], x \mid M \text{ accepts } x \text{ in } f(|x|) \text{ steps}\}$$

where  $[M]$  is a description of  $M$  in some fixed encoding scheme.

Then, we can show

$$H_f \in \text{TIME}(f(n)^3) \text{ and } H_f \notin \text{TIME}(f(\lfloor n/2 \rfloor))$$

### Time Hierarchy Theorem

For any constructible function  $f(n) \geq n$ ,  $\text{TIME}(f(n))$  is properly contained in  $\text{TIME}(f(2n + 1)^3)$ .

## Strong Hierarchy Theorems

For any constructible function  $f(n) \geq n$ ,  $\text{TIME}(f(n))$  is properly contained in  $\text{TIME}(f(n)(\log f(n)))$ .

### Space Hierarchy Theorem

For any pair of constructible functions  $f$  and  $g$ , with  $f = O(g)$  and  $g \neq O(f)$ , there is a language in  $\text{SPACE}(g(n))$  that is not in  $\text{SPACE}(f(n))$ .

Similar results can be established for nondeterministic time and space classes.

## Consequences

- For each  $k$ ,  $\text{TIME}(n^k) \neq \text{TIME}(n^{k+1})$ .
- $P \neq \text{EXP}$ .
- $L \neq \text{PSPACE}$ .
- Any language that is  $\text{EXP}$ -complete is not in  $P$ .
- There are no problems in  $P$  that are complete under linear time reductions.

## P-complete Problems

It makes little sense to talk of complete problems for the class  $P$  with respect to polynomial time reducibility  $\leq_P$ .

There are problems that are complete for  $P$  with respect to *logarithmic space* reductions  $\leq_L$ .

One example is  $CVP$ —the circuit value problem.

- If  $CVP \in L$  then  $L = P$ .
- If  $CVP \in NL$  then  $NL = P$ .