

Concepts in Programming Languages

Marcelo Fiore

Computer Laboratory
University of Cambridge

Lent 2008

<http://www.cl.cam.ac.uk/teaching/0708/ConceptsPL/>

/ 1

Practicalities

◆ Topics.

1. Introduction and motivation.
2. The first *procedural* language: FORTRAN (1954–58).
3. The first *declarative* language: LISP (1958–62).
4. *Block-structured* procedural languages: Algol (1958–68), Pascal (1970).
5. *Object-oriented* languages — Concepts and origins: Simula (1964–67), Smalltalk (1971–80).
6. *Types, data abstraction*, and *modularity*: C++ (1983–98), SML (1984–97).
7. The *state of the art*: Scala (2007)

/ 3

Main books

- ◆ J. C. Mitchell. *Concepts in programming languages*. Cambridge University Press, 2003.
- ◆ T. W. Pratt and M. V. Zelkowitz. *Programming Languages: Design and implementation* (3RD EDITION). Prentice Hall, 1999.
- ◆ R. Sethi. *Programming languages: Concepts & constructs* (2ND EDITION). Addison-Wesley, 1996.

/ 2

◆ 2 exam questions.

◆ Course web page:

www.cl.cam.ac.uk/teaching/0708/ConceptsPL/

with lecture slides and reading material.

/ 4

Topic I

Introduction and motivation

References:

- ◆ Chapter 1 of *Concepts in programming languages* by J. C. Mitchell. CUP, 2003.
- ◆ Chapter 1 of *Programming languages: Design and implementation* (3RD EDITION) by T. W. Pratt and M. V. Zelkowitz. Prentice Hall, 1999.

/ 5

Why study programming languages?

- ◆ To improve the ability to develop effective algorithms.
- ◆ To improve the use of familiar languages.
- ◆ To increase the vocabulary of useful programming constructs.
- ◆ To allow a better choice of programming language.
- ◆ To make it easier to learn a new language.
- ◆ To make it easier to design a new language.

/ 7

Goals

- ◆ Critical *thinking* about programming languages.
 - What is a programming language!?
- ◆ *Study* programming languages.
 - ◆ Be familiar with basic language *concepts*.
 - ◆ Appreciate trade-offs in language *design*.
- ◆ Trace *history*, appreciate *evolution* and diversity of *ideas*.
- ◆ Be prepared for new programming *methods*, *paradigms*.

/ 6

What makes a good language?

- ◆ Clarity, simplicity, and unity.
- ◆ Orthogonality.
- ◆ Naturalness for the application.
- ◆ Support of abstraction.
- ◆ Ease of program verification.
- ◆ Programming environments.
- ◆ Portability of programs.

/ 8

Influences

- ◆ Cost of use.
 - ◆ Cost of execution.
 - ◆ Cost of program translation.
 - ◆ Cost of program creation, testing, and use.
 - ◆ Cost of program maintenance.
- ◆ Computer capabilities.
- ◆ Applications.
- ◆ Programming methods.
- ◆ Implementation methods.
- ◆ Theoretical studies.
- ◆ Standardisation.

/ 9

/ 10

Applications domains

Era	Application	Major languages	Other languages
1960s	Business	COBOL	Assembler
	Scientific	FORTRAN	ALGOL, BASIC, APL
	System	Assembler	JOVIAL, Forth
	AI	LISP	SNOBOL
Today	Business	COBOL, SQL, spreadsheet	C, PL/I, 4GLs
	Scientific	FORTRAN, C, C++ Maple, Mathematica	BASIC, Pascal
	System	BCPL, C, C++	Pascal, Ada, BASIC, MODULA
	AI	LISP, Prolog	
	Publishing	T _E X, Postscript, word processing	
	Process	UNIX shell, TCL, Perl	Marvel, Esterel
	New paradigms	Smalltalk, ML, Haskell, Java Python, Ruby	Eifell, C#, Scala

Motivating application in language design

A specific purpose provides *focus* for language designers; it helps to set criteria for making design decisions.

A specific, motivating application also helps to solve one of the hardest problems in programming language design: deciding which features to leave out.

/ 11

/ 12

Examples: Good languages designed with a specific purpose in mind.

- ◆ **LISP:** symbolic computation, automated reasoning
- ◆ **FP:** functional programming, algebraic laws
- ◆ **BCPL:** compiler writing
- ◆ **Simula:** simulation
- ◆ **C:** systems programming
- ◆ **ML:** theorem proving
- ◆ **Smalltalk:** Dynabook
- ◆ **Clu, ML module system:** modular programming
- ◆ **C++:** object orientation
- ◆ **Java:** Internet applications

/ 13

Theoretical foundations

Examples:

- ◆ Formal-language theory.
- ◆ Automata theory.
- ◆ Algorithmics.
- ◆ λ -calculus.
- ◆ Semantics.
- ◆ Formal verification.
- ◆ Type theory.
- ◆ Complexity theory.

/ 15

Program execution model

Good language design presents *abstract machine*.

- ◆ **FORTRAN:** Flat register machine; memory arranged as linear array
- ◆ **LISP:** cons cells, read-eval-print loop
- ◆ **Algol** family: stack of activation records; heap storage
- ◆ **BCPL, C:** underlying machine + abstractions
- ◆ **Simula:** Object references
- ◆ **FP, ML:** functions are basic control structure
- ◆ **Smalltalk:** objects and methods, communicating by messages
- ◆ **Java:** Java virtual machine

/ 14

Standardisation

- ◆ Proprietary standards.
- ◆ Consensus standards.
 - ◆ ANSI.
 - ◆ IEEE.
 - ◆ BSI.
 - ◆ ISO.

/ 16

Language standardisation

Consider: `int i; i = (1 && 2) + 3 ;`

? Is it valid C code? If so, what's the value of `i`?

? How do we answer such questions!?

! Read the reference manual.

! Try it and see!

! Read the ANSI C Standard.

Language-standards issues

Timeliness. When do we standardise a language?

Conformance. What does it mean for a program to adhere to a standard and for a compiler to compile a standard?

Ambiguity and freedom to optimise — Machine dependence — Undefined behaviour.

Obsolescence. When does a standard age and how does it get modified?

Deprecated features.

/ 17

/ 18

Language standards PL/1

? What does the following

`9 + 8/3`

mean?

- 11.666... ?
- **Overflow** ?
- 1.666... ?

`DEC(p, q)` means `p` digits with `q` after the decimal point.

Type rules for `DECIMAL` in PL/1:

`DEC(p1, q1) + DEC(p2, q2)`

=> `DEC(MIN(1+MAX(p1-q1, p2-q2)+MAX(q1, q2), 15), MAX(q1, q2))`

`DEC(p1, q1) / DEC(p2, q2)`

=> `DEC(15, 15-((p1-q1)+q2))`

/ 19

/ 20

For $9 + 8/3$ we have:

```
DEC(1,0) + DEC(1,0)/DEC(1,0)
=> DEC(1,0) + DEC(15,15-((1-0)+0))
=> DEC(1,0) + DEC(15,14)
=> DEC(MIN(1+MAX(1-0,15-14)+MAX(0,14),15),MAX(0,14))
=> DEC(15,14)
```

So the calculation is as follows

```
9 + 8/3
= 9 + 2.6666666666666666
= 11.666666666666666 - OVERFLOW
= 1.6666666666666666 - OVERFLOW disabled
```

/ 21

1981–85: Smalltalk-80, Prolog, Ada 83.

1986–90: C++, **SML**, Haskell.

1991–95: Ada 95, TCL, Perl.

1996–2000: Java.

2000–05: C#, Python, Ruby, **Scala**.

/ 23

History

1951–55: Experimental use of expression compilers.

1956–60: **FORTRAN**, COBOL, **LISP**, **Algol 60**.

1961–65: APL notation, Algol 60 (revised), SNOBOL, CPL.

1966–70: APL, SNOBOL 4, FORTRAN 66, BASIC, **SIMULA**, Algol 68, Algol-W, BCPL.

1971–75: **Pascal**, PL/1 (Standard), C, Scheme, Prolog.

1976–80: **Smalltalk**, Ada, FORTRAN 77, ML.

/ 22

Language groups

◆ Multi-purpose languages

- ◆ Scala, C#, Java, C++, C
- ◆ Haskell, ML, Scheme, LISP

◆ Scripting languages

- ◆ Perl, TCL, UNIX shell

◆ Special-purpose languages

- ◆ SQL
- ◆ \LaTeX

/ 24

Things to think about

- ◆ What makes a good language?
- ◆ The role of
 1. motivating applications,
 2. program execution,
 3. theoretical foundationsin language design.
- ◆ Language standardisation.

/ 25

FORTRAN = FORMula TRANslator (1957)

- ◆ The first high-level programming language to become widely used.
- ◆ Developed in the 1950s by an IBM team led by John Backus.
- ◆ At the time the utility of any high-level language was open to question!

The main complain was the efficiency of compiled code. This heavily influenced the designed, orienting it towards providing execution efficiency.

- ◆ Standards:
1966, 1977 (FORTRAN 77), 1990 (FORTRAN 90).

/ 27

Topic II

FORTRAN : A simple procedural language

References:

- ◆ **Chapter 10(§1)** of *Programming Languages: Design and implementation* (3RD EDITION) by T. W. Pratt and M. V. Zelkowitz. Prentice Hall, 1999.

/ 26

John Backus

As far as we were aware, we simply made up the language as we went along. We did not regard **language design** as a difficult problem, merely a simple prelude to the real problem: designing a compiler which could produce efficient programs.^a

^aIn R. L. Wexelblat, *History of Programming Languages*, Academic Press, 1981, page 30.

/ 28

Overview

Execution model

- ◆ FORTRAN program = main program + subprograms
 - ◆ Each is *compiled separate* from all others.
 - ◆ Translated programs are linked into final executable form during loading.
- ◆ All *storage is allocated statically* before program execution begins; no run-time storage management is provided.
- ◆ Flat register machine. *No stacks, no recursion*. Memory arranged as linear array.

/ 29

Overview

Data types

- ◆ Numeric data: Integer, real, complex, double-precision real.
- ◆ Boolean data. called logical
- ◆ Arrays. of fixed declared length
- ◆ Character strings. of fixed declared length
- ◆ Files.

/ 30

Overview

Control structures

- ◆ FORTRAN 66
 - Relied heavily on statement labels and `GOTO` statements.
- ◆ FORTRAN 77
 - Added some modern control structures (e.g., conditionals).

/ 31

Example

```
PROGRAM MAIN
  PARAMETER (MaXsIz=99)
  REAL A(mAxSiZ)
10  READ (5,100,END=999) K
100 FORMAT(I5)
    IF (K.LE.0 .OR. K.GT.MAXSIZ) STOP
    READ *, (A(I), I=1, K)
    PRINT *, (A(I), I=1, K)
    PRINT *, 'SUM=', SUM(A, K)
    GO TO 10
999 PRINT *, "All Done"
    STOP
    END
```

/ 32

Example Commentary

```
C SUMMATION SUBPROGRAM
  FUNCTION SUM(V,N)
    REAL V(N)
    SUM = 0.0
    DO 20 I = 1,N
      SUM = SUM + V(I)
20    CONTINUE
    RETURN
  END
```

- ◆ Columns and lines are relevant.
- ◆ Blanks are ignored (by early FORTRANs).
- ◆ Variable names are from 1 to 6 characters long, begin with a letter, and contain letters and digits.
- ◆ Programmer-defined constants.
- ◆ Arrays: when sizes are given, lower bounds are assumed to be 1; otherwise subscript ranges must be explicitly declared.
- ◆ Variable types may not be declared: implicit naming convention.

/ 33

/ 34

- ◆ Data formats.
- ◆ FORTRAN 77 has no `while` statement.
- ◆ Functions are compiled separately from the main program. Information from the main program is not used to pass information to the compiler. Failure may arise when the loader tries to merge subprograms with main program.
- ◆ Function parameters are uniformly transmitted by reference (or value-result).
Recall that allocation is done statically.
- ◆ `DO` loops by increment.
- ◆ A value is returned in a FORTRAN function by assigning a value to the name of a function.

On syntax

A misspelling bug ...

```
do 10 i = 1,100    vs.    do 10 i = 1.100
```

... that is reported to have caused a rocket to explode
upon launch into space!

/ 35

/ 36

Types

- ◆ FORTRAN has no mechanism for creating user types.

- ◆ *Static type checking* is used in FORTRAN, but the checking is incomplete.

Many language features, including arguments in subprogram calls and the use of `COMMON` blocks, cannot be statically checked (in part because subprograms are compiled independently).

Constructs that cannot be statically checked are ordinarily left unchecked at run time in FORTRAN implementations.

/ 37

The sequential storage representation is critical in the definition of the `EQUIVALENCE` and `COMMON` declarations.

- ◆ `EQUIVALENCE`

This declaration allows more than one simple or subscripted variable to refer to the same storage location.

Is this a good idea?

Consider the following:

```
REAL X
INTEGER Y
EQUIVALENCE (X,Y)
```

/ 39

Storage

Representation and Management

- ◆ Storage representation in FORTRAN is *sequential*.

- ◆ Only two levels of referencing environment are provided, *global* and *local*.

The global environment may be partitioned into separate *common* environments that are shared amongst sets of subprograms, but only data objects may be shared in this way.

/ 38

- ◆ `COMMON`

The global environment is set up in terms of *sets of variables and arrays*, which are termed *COMMON blocks*.

A `COMMON` block is a named block of storage and may contain the values of any number of simple variables and arrays.

`COMMON` blocks may be used to isolate global data to only a few subprograms needing that data.

Is the `COMMON` block a good idea?

Consider the following:

```
COMMON/BLK/X, Y, K(25)           in MAIN
COMMON/BLK/U, V, I(5), M(4,5)   in SUB
```

/ 40

Aliasing

Aliasing occurs when two names or expressions refer to the same object or location.

- ◆ Aliasing raises serious problems for both the user and implementor of a language.
- ◆ Because of the problems caused by aliasing, new language designs sometimes attempt to restrict or eliminate altogether features that allow aliases to be constructed.^a

^aIn what regards to the problem of checking for aliasing, interested students may wish to investigate the work on the programming language *Euclid* and/or the work of John Reynolds and followers on *Syntactic Control of Interference*.

/ 41

FORTRAN subroutines and functions

- ◆ *Actual parameters* may be simple variables, literals, array names, subscripted variables, subprogram names, or arithmetic or logical expressions.

The interpretation of a *formal parameter* as an array is done by the called subroutine.

- ◆ Each subroutine is compiled independently and no checking is done for compatibility between the subroutine declaration and its call.

/ 43

Parameters

There are two concepts that must be clearly distinguished.

- ◆ The parameter names used in a function declaration are called *formal parameters*.
- ◆ When a function is called, expressions called *actual parameters* are used to compute the parameter values for that call.

/ 42

- ◆ The language specifies that if a formal parameter is assigned to, the actual parameter must be a variable, but because of independent compilation this rule cannot be checked by the compiler.

Example:

```
SUBROUTINE SUB(X,Y)
  X = Y
END
```

```
CALL SUB(-1.0,1.0)
```

- ◆ Parameter passing is uniformly by *reference*.

/ 44

Topic III

LISP: functions, recursion, and lists

References:

- ◆ Chapter 3 of *Concepts in programming languages* by J. C. Mitchell. CUP, 2003.
- ◆ Chapters 5(§4.5) and 13(§1) of *Programming languages: Design and implementation* (3RD EDITION) by T. W. Pratt and M. V. Zelkowitz. Prentice Hall, 1999.

- ◆ J. McCarthy. Recursive functions of symbolic expressions and their computation by machine. *Communications of the ACM*, 3(4):184–195, 1960.^a

^aAvailable on-line from (<http://www-formal.stanford.edu/jmc/recursive.html>).

/ 45

LISP = LISt Processing (±1960)

- ◆ Developed in the late 1950s and early 1960s by a team led by John McCarthy in MIT.
- ◆ McCarthy described LISP as a “a scheme for representing the *partial recursive functions* of a certain class of symbolic expressions”.
- ◆ Motivating problems: Symbolic computation (*symbolic differentiation*), logic (*Advice taker*), experimental programming.
- ◆ Software embedding LISP: Emacs (text editor), GTK (linux graphical toolkit), Sawfish (window manager), GnuCash (accounting software).

/ 47

Programming-language phrases

- ◆ *Expressions*. A syntactic entity that may be evaluated to determine its value.
- ◆ *Statement*. A command that alters the state of the machine in some explicit way.
- ◆ *Declaration*. A syntactic entity that introduces a new identifier, often specifying one or more attributes.

/ 46

/ 48

Innovation in the design of LISP

- ◆ LISP is an expression-based language.
Conditional expressions that produce a value were new in LISP.
- ◆ *Pure* LISP has no statements and no expressions with side effects. However, LISP also supports *impure* constructs.

/ 49

Overview

- ◆ LISP syntax is extremely simple. To make parsing easy, all operations are written in prefix form (*i.e.*, with the operator in front of all the operands).
- ◆ LISP programs compute with *atoms* and *cells*.
- ◆ The basic data structures of LISP are *dotted pairs*, which are pairs written with a dot between the components. Putting atoms or pairs together, one can write symbolic expressions in a form traditionally called *S-expressions*. Most LISP programs use *lists* built out of S-expressions.
- ◆ LISP is an *untyped* programming language.

/ 51

Some contributions of LISP

- ◆ Lists.
- ◆ Recursive functions.
- ◆ Garbage collection.
- ◆ Programs as data.

/ 50

- ◆ Most operations in LISP take list arguments and return list values.

Example:

```
( cons '(a b c) '(d e f) )
```

cons-cell representation

- ◆ **Remark:** The function `(quote x)`, or simply `'x`, just returns the literal value of its argument.

/ 52

? How does one recognise a LISP program?

```
( defvar x 1 )
( defun g(z) (+ x z) )
( defun f(y)
  ( + ( g y )
    ( let
      ( ( x y ) )
      ( g x )
    ) ) )
( f (+ x 1) )

val x = 1 ;
fun g(z) = x + z ;
fun f(y)
  = g(y) +
  let
    val x = y
  in
    g(x)
  end ;
f(x+1) ;
```

! It is full of parentheses!

Static and dynamic scope

Static scope rules relate references with declarations of names in the program text; *dynamic scope* rules relate references with associations for names during program execution.

There are two main rules for finding the declaration of a global identifier:

- ◆ *Static scope*. A global identifier refers to the identifier with that name that is declared in the closest enclosing scope of the program text.
- ◆ *Dynamic scope*. A global identifier refers to the identifier associated with the most recent environment.

Historically, LISP was a *dynamically scoped* language ...

```
( defvar x T )
( defun test(y) (eq x y) )
( cond
  ( x ( let ( (z 0) ) (test z) ) )
)
```

vs.

```
( defvar x T )
( defun test(y) (eq x y) )
( cond
  ( x ( let ( (x 0) ) (test x) ) )
)
```

...when *Scheme* was introduced in 1978, it was a *statically scoped* variant of LISP.

Renaming of local variables

Lexical scope is deeply related to renaming of variables. It should not matter whether a program uses one name or another one for a local variable. Let us state this supposition as a principle:

Consistent renaming of local names in the source text has no effect on the computation set up by a program.

This *renaming principle* motivates static scope because a language that obeys the renaming principle uses lexical scope. The reason is that the renaming principle can be applied to rename local variables until each name has only one declaration in the entire program. This one declaration is the one obtained under lexical scope.

The importance of static scope

Static scope rules play an important part in the design and implementation of most programming languages.

- ◆ Static scope rules allow many different sorts of connections to be established between references to names and their declarations during translation.

For instance, relating a variable name to a declaration for the variable and relating a constant name to a declaration for the constant.

Other connections include relating names to type declarations, relating formal parameters to formal

/ 57

Abstract machines

The terminology *abstract machine* is generally used to refer to an idealised computing device that can execute a specific programming language directly.

Typically an abstract machine may not be fully implementable. However, an abstract machine should be sufficiently realistic to provide useful information about the real execution of programs.

An important goal in discussing abstract machines is to identify the mental model of the computer that a programmer uses to write and debug programs.

/ 59

parameter specifications, relating subprogram calls to subprogram declarations, and relating statement labels referenced in `goto` statements to labels on particular statements.

In each of these cases, a different set of simplifications may be made during translation that make execution of the program more efficient.

- ◆ Static scope rules are also important for the programmer in reading a program because they make it possible to relate a name referenced in a program to a declaration for the name without tracing the course of program execution.

/ 58

LISP abstract machine

The abstract machine for Pure LISP has four parts:

1. A *LISP* expression to be evaluated.
2. A *continuation*, which is a function representing the remaining of the program to evaluate when done with the current expression.
3. An *association list*, also known as the *A-list*.
The purpose of the A-list is to store the values of variables that may occur either in the current expression to be evaluated or in the remaining expressions in the program.
4. A *heap*, which is a set of *cons cells* (or *dotted pairs*) that might be pointed to by pointers in the A-list.

/ 60

Recursion

McCarthy (1960)

```
( defun subst ( x y z )  
  ( cond  
    ( ( atom z ) ( cond ( ( eq z y ) x ) ( T z ) ) )  
    ( T ( cons (subst x y (car z)) (subst x y (cdr z)) ) ) )  
  )  
)
```

In general . . . , the routine for a recursive function uses itself as a subroutine. For example, the program for `subst x y z` uses itself as a subroutine to evaluate the result of substituting into the subexpression `car z` and `cdr z`. While `subst x y (cdr z)` is being evaluated, the result of the previous evaluation of `subst x y (car z)` must be saved in a temporary storage register. However, `subst` may need the same register for evaluating

/ 61

Garbage collection

McCarthy (1960)

. . . When a free register is wanted, and there is none left on the free-storage list, a reclamation[†] cycle starts.

[†] We already called this process “garbage collection”, but I guess that I chickened out of using it in the paper—or else the Research Laboratory of Electronics grammar ladies wouldn’t let me.

/ 63

`subst x y (cdr z)`. This possible conflict is resolved by the SAVE and UNSAVE routines that use the *public push-down list*^a. The SAVE routine has an index that tells it how many registers in the push-down list are already in use. It moves the contents of the registers which are to be saved to the first unused registers in the push-down list, advances the index of the list, and returns to the program form which control came. This program may then freely use these registers for temporary storage. Before the routine exits it uses UNSAVE, which restores the contents of the temporary registers from the push-down list and moves back the index of this list. The result of these conventions is described, in programming terminology, by saying that the recursive subroutine is transparent to the temporary storage registers.

^a1995: now called a stack

/ 62

Garbage collection

In computing, *garbage* refers to memory locations that are not accessible to a program.

At a given point in the execution of a program P, a memory location ℓ is *garbage* if no completed execution of P from this point can access location ℓ . In other words, replacing the contents of ℓ or making this location inaccessible to P cannot affect any further execution of the program.

Garbage collection is the process of detecting garbage during the execution of a program and making it available.

/ 64

Parameter passing in LISP

The *actual parameters* in a function call are always expressions, represented as lists structures.

LISP provides two main methods of *parameter passing*:

- ◆ *Pass/Call-by-value*. The most common method is to evaluate the expressions in the actual-parameter list, and pass the resulting values.
- ◆ *Pass/Call-by-name*.* A less common method is to transmit the expression in the actual parameter list *unevaluated*, and let the call function evaluate them as needed using `eval`.

The programmer may specify transmission by name using `nlambda` in place of `lambda` in the function definition.

Programs as data

- ◆ LISP data and LISP program have the same syntax and internal representation. This allows data structures to be executed as programs and programs to be modified as data.
- ◆ One feature that sets LISP apart from many other languages is that it is possible for a program to build a data structure that represents an expression and then evaluates the expression as if it were written as part of the program. This is done with the function `eval`.

/ 65

Strict and lazy evaluation

Example: Consider the following function definitions with parameter-passing by value.

```
( defun CountFrom(n) ( CountFrom(+ n 1) ) )
```

```
( defun FunnyOr(x y)
  ( cond ( x 1) ( T y ) )
)
```

```
( defun FunnyOrelse(x y)
  ( cond ( (eval x) 1) ( T (eval y) ) )
)
```

/ 67

? What happens in the following calls?

```
( FunnyOr T (CountFrom 0) )
```

```
( FunnyOr nil T )
```

```
( FunnyOrelse 'T '(CountFrom 0) )
```

```
( FunnyOrelse 'nil 'T )
```

/ 66

/ 68

Topic IV

Block-structured procedural languages Algol and Pascal

References:

- ◆ **Chapters 5 and 7**, of *Concepts in programming languages* by J. C. Mitchell. CUP, 2003.
- ◆ **Chapters 10(§2) and 11(§1)** of *Programming languages: Design and implementation* (3RD EDITION) by T. W. Pratt and M. V. Zelkowitz. Prentice Hall, 1999.

/ 69

Parameters

There are two concepts that must be clearly distinguished:

- ◆ A *formal parameter* is a declaration that appears in the declaration of the subprogram. (The computation in the body of the subprogram is written in terms of formal parameters.)
- ◆ An *actual parameter* is a value that the calling program sends to the subprogram.

Example: Named parameter associations.

Normally the actual parameters in a subprogram call are just listed and the matching with the formal parameters is done by

/ 71

- ◆ **Chapter 5** of *Programming languages: Concepts & constructs* by R. Sethi (2ND EDITION). Addison-Wesley, 1996.
- ◆ **Chapter 7** of *Understanding programming languages* by M Ben-Ari. Wiley, 1996.

/ 70

position:

```
procedure Proc(First: Integer; Second: Character);  
Proc(24, 'h');
```

In *Ada* it is possible to use *named association* in the call:

```
Proc(Second => 'h', First => 24);
```

? What about in *ML*? Can it be simulated?

This is commonly used together with *default parameters*:

```
procedure Proc(First: Integer := 0; Second: Character := '*');  
Proc(Second => 'o');
```

/ 72

Named associations and default parameters are commonly used in the command languages of operating systems, where each command may have dozens of options and normally only a few parameters need to be explicitly changed. However, there are dangers with this programming style. The use of default parameters can make a program hard to read because calls whose syntax is different actually call the same subprogram. Name associations are problematic because they bind the subprogram declaration and the calls more tightly than is usually needed. If you use only positional parameters in calling subprograms from a library, you could buy a competing library and just recompile or link. However, if you use named parameters, then you might have to do extensive modifications to your program to conform to the new parameter names.

/ 73

Parameter passing

Pass/Call-by-value

- ◆ In *pass-by-value*, the actual parameter is evaluated. The value of the actual parameter is then stored in a new location allocated for the function parameter.
- ◆ Under *call-by-value*, a formal parameter corresponds to the value of an actual parameter. That is, the formal x of a procedure P takes on the value of the actual parameter.

The idea is to evaluate a call $P(E)$ as follows:

$x := E;$

execute the body of procedure P ;

if P is a function, return a result.

/ 75

Parameter passing

The way that actual parameters are evaluated and passed to procedures depends on the programming language and the kind of *parameter-passing mechanisms* it uses.

The main distinction between different parameter-passing mechanisms are:

- ◆ the time that the actual parameter is evaluated, and
- ◆ the location used to store the parameter value.

NB: The *location* of a variable (or expression) is called its *L-value*, and the *value* stored in this location is called the *R-value* of the variable (or expression).

/ 74

Parameter passing

Pass/Call-by-reference

1. In *pass-by-reference*, the actual parameter must have an L-value. The L-value of the actual parameter is then bound to the formal parameter.
2. Under *call-by-reference*, a formal parameter becomes a synonym for the location of an actual parameter. An actual reference parameter must have a location.

/ 76

Example:

```
program main;
begin
  function f( var x: integer; y: integer): integer;
  begin
    x := 2;
    y := 1;
    if x = 1 then f := 1 else f:= 2
  end;

  var z: integer;
  z := 0;
  writeln( f(z,z) )
end
```

/ 77

- ◆ **Efficiency.** Pass-by-value may be inefficient for large structures if the value of the large structure must be copied. Pass-by-reference maybe less efficient than pass-by-value for small structures that would fit directly on stack, because when parameters are passed by reference we must dereference a pointer to get their value.

/ 79

The difference between **call-by-value** and **call-by-reference** is important to the programmer in several ways:

- ◆ **Side effects.** Assignments inside the function body may have different effects under pass-by-value and pass-by-reference.
- ◆ **Aliasing.** Aliasing occurs when two names refer to the same object or location.

Aliasing may occur when two parameters are passed by reference or one parameter passed by reference has the same location as the global variable of the procedure.

/ 78

Parameter passing

Pass/Call-by-value/result

Call-by-value/result is also known as *copy-in/copy-out* because the actuals are initially copied into the formals and the formals are eventually copied back out to the actuals.

Actuals that do not have locations are passed by value.

Actuals with locations are treated as follows:

1. **Copy-in phase.** Both the values and the locations of the actual parameters are computed. The values are assigned to the corresponding formals, as in call-by-value, and the locations are saved for the copy-out phase.
2. **Copy-out phase.** After the procedure body is executed, the final values of the formals are copied back out to the locations computed in the copy-in phase.

/ 80

Examples:

- ◆ A parameter in **Pascal** is normally passed by value. It is passed by reference, however, if the keyword `var` appears before the declaration of the formal parameter.

```
procedure proc(in: Integer; var out: Real);
```

- ◆ The only parameter-passing method in **C** is call-by-value; however, the effect of call-by-reference can be achieved using pointers. In C++ true call-by-reference is available using *reference parameters*.

/ 81

Parameter passing

Pass/Call-by-name

The **Algol 60** report describes *call-by-name* as follows:

1. Actual parameters are textually substituted for the formals. Possible conflicts between names in the actuals and local names in the procedure body are avoided by renaming the locals in the body.
2. The resulting procedure body is substituted for the call. Possible conflicts between nonlocals in the procedure body and locals at the point of call are avoided by renaming the locals at the point of call.

/ 83

- ◆ **Ada** supports three kinds of parameters:

1. **in** parameters, corresponding to value parameters;
2. **out** parameters, corresponding to just the copy-out phase of call-by-value/result; and
3. **in out** parameters, corresponding to either reference parameters or value/result parameters, at the discretion of the implementation.

/ 82

Block structure

- ◆ In a *block-structured language*, each program or subprogram is organised as a set of nested blocks. A *block* is a region of program text, identified by begin and end markers, that may contain declarations local to this region.
- ◆ *In-line (or unnamed) blocks* are useful for restricting the scope of variables by declaring them only when needed, instead of at the beginning of a subprogram. The trend in programming is to reduce the size of subprograms, so the use of unnamed blocks is less useful than it used to be.

/ 84

Nested procedures can be used to group statements that are executed at more than one location within a subprogram, but refer to local variables and so cannot be external to the subprogram. Before modules and object-oriented programming were introduced, nested procedures were used to structure large programs.

- ◆ Block structure was first defined in [Algol](#). [Pascal](#) contains nested procedures but not in-line blocks; [C](#) contains in-line blocks but not nested procedures; [Ada](#) supports both.
- ◆ *Block-structured languages* are characterised by the following properties:
 - ◆ New variables may be declared at various points in a program.

/ 85

Algol

HAD A MAJOR EFFECT ON LANGUAGE DESIGN

- ◆ The Algol-like programming languages evolved in parallel with the LISP family of languages, beginning with Algol 58 and Algol 60 in the late 1950s.
- ◆ The most prominent Algol-like programming languages are Pascal and C, although C differs from most of the Algol-like languages in some significant ways. Further Algol-like languages are: Algol 58, Algol W, Euclid, *etc.*

/ 87

- ◆ Each declaration is visible within a certain region of program text, called a block.
- ◆ When a program begins executing the instructions contained in a block at run time, memory is allocated for the variables declared in that block.
- ◆ When a program exits a block, some or all of the memory allocated to variables declared in that block will be deallocated.
- ◆ An identifier that is not declared in the current block is considered global to the block and refers to the entity with this name that is declared in the closest enclosing block.

/ 86

- ◆ The *main characteristics* of the Algol family are:
 - ◆ the familiar semicolon-separated sequence of statements,
 - ◆ block structure,
 - ◆ functions and procedures, and
 - ◆ static typing.

/ 88

Algol 60

- ◆ Designed by a committee (including Backus, McCarthy, Perlis) between 1958 and 1963.
 - ◆ Intended to be a general purpose programming language, with emphasis on scientific and numerical applications.
 - ◆ Compared with FORTRAN, Algol 60 provided better ways to represent *data structures* and, like LISP, allowed functions to be called recursively.
- Eclipsed by FORTRAN because of the lack of I/O statements, separate compilation, and library; and because it was not supported by IBM.

/ 89

Algol 60 Some trouble spots

- ◆ The Algol 60 type discipline had some shortcomings. For instance:
 - ◆ Automatic type conversions were not fully specified (*e.g.*, $x := x/y$ was not properly defined when x and y were integers—is it allowed, and if so was the value rounded or truncated?).
 - ◆ The type of a procedure parameter to a procedure does not include the types of parameters.
 - ◆ An array parameter to a procedure is given type array, without array bounds.

/ 91

Algol 60 Features

- ◆ Simple statement-oriented syntax.
- ◆ Block structure.
- ◆ Recursive functions and stack storage allocation.
- ◆ Fewer ad hoc restrictions than previous languages (*e.g.*, general expressions inside array indices, procedures that could be called with procedure parameters).
- ◆ A primitive *static type system*, later improved in Algol 68 and Pascal.

/ 90

- ◆ Algol 60 was designed around two parameter-passing mechanisms, *call-by-name* and *call-by-value*. Call-by-name interacts badly with side effects; call-by-value is expensive for arrays.
- ◆ There are some awkward issues related to control flow, such as memory management, when a program jumps out of a nested block.

/ 92

Algol 60 procedure types^a

In Algol 60, the type of each formal parameter of a procedure must be given. However, `proc` is considered a type (the type of procedures). This is much simpler than the ML types of function arguments. However, this is really a type loophole; because calls to procedure parameters are not fully type checked, Algol 60 programs may produce run-time errors.

Write a procedure declaration for `Q` that causes the following program fragment to produce a run-time type error:

```
proc P ( proc Q )
  begin Q(true) end;

P(Q);
```

where `true` is a Boolean value. Explain why the procedure is statically type correct, but produces a run-time type error. (You may assume that adding a Boolean to an integer is a run-time error.)

^aExercise 5.1 of *Concepts in programming languages* by J. Mitchell, CUP, 2003.

/ 93

Algol 60 pass-by-name^a

The following Algol 60 code declares a procedure `P` with one pass-by-name integer parameter. Explain how the procedure call `P(A[i])` changes the values of `i` and `A` by substituting the actual parameters for the formal parameters, according to the Algol 60 copy rule. What integer values are printed by the program? And, by using pass-by-value parameter passing?

```
begin
  integer i; i:=1;
  integer array A[1:2]; A[1]:=2; A[2]:=3;

  procedure P(x); integer x;
    begin i:=x; x:=1 end

  P(A[i]); print(i,A[1],A[2])
end
```

^aExercise 5.2 of *Concepts in programming languages* by J. Mitchell, CUP, 2003.

/ 95

Algol 60 pass-by-name

Copy rule

```
real procedure sum(E,i,low,high); value low, high;
  real E; integer i, low, high;
  begin
    sum:=0.0; for i := low step 1 until high do sum := sum+E;
  end
```

```
integer j; real array A[1:10]; real result;
for j:= 1 step 1 until 10 do A[j] := j;
result := sum(A[j],j,1,10)
```

By the *Algol 60 copy rule*, the function call to `sum` above is equivalent to:

```
begin
  sum:=0.0; for j := 1 step 1 until 10 do sum := sum+A[j];
end
```

/ 94

Algol 68

- ◆ Intended to remove some of the difficulties found in Algol 60 and to improve the expressiveness of the language.

It did not entirely succeed however, with one main problem being the difficulty of efficient compilation (e.g., the implementation consequences of higher-order procedures where not well understood at the time).

- ◆ One contribution of Algol 68 was its *regular, systematic type system*.

The types (referred to as *modes* in Algol 68) are either *primitive* (int, real, complex, bool, char, string, bits, bytes, semaphore, format, file) or *compound* (array, structure, procedure, set, pointer).

/ 96

Type constructions could be combined without restriction. This made the type system seem more systematic than previous languages.

- ◆ Algol 68 memory management involves a *stack* for local variables and *heap* storage. Algol 68 data on the heap are explicitly allocated, and are reclaimed by *garbage collection*.
- ◆ Algol 68 parameter passing is by value, with pass-by-reference accomplished by pointer types. (This is essentially the same design as that adopted in C.)
- ◆ The decision to allow independent constructs to be combined without restriction also led to some complex features, such as assignable pointers.

/ 97

Pascal

- ◆ Designed in the 1970s by Niklaus Wirth, after the design and implementation of Algol W.
- ◆ Very successful programming language for *teaching*, in part because it was designed explicitly for that purpose. Also designed to be compiled in one pass. This hindered language design; *e.g.*, it forced the problematic *forward* declaration.
- ◆ Pascal is a *block-structured* language in which *static scope* rules are used to determine the meaning of nonlocal references to names.

/ 99

Algol innovations

- ◆ Use of BNF syntax description.
- ◆ Block structure.
- ◆ Scope rules for local variables.
- ◆ Dynamic lifetimes for variables.
- ◆ Nested *if-then-else* expressions and statements.
- ◆ Recursive subroutines.
- ◆ Call-by-value and call-by-name arguments.
- ◆ Explicit type declarations for variables.
- ◆ Static typing.
- ◆ Arrays with dynamic bounds.

/ 98

- ◆ A Pascal program is always formed from a single main program block, which contains within it definitions of the subprograms used. Each block has a characteristic *structure*: a header giving the specification of parameters and results, followed by constant definitions, type definitions, local variable declarations, other nested subprogram definitions, and the statements that make up the executable part.
- ◆ Pascal is a *quasi-strong, statically typed* programming language. An important contribution of the Pascal *type system* is the rich set of data-structuring concepts: *e.g.* enumerations, subranges, records, variant records, sets, sequential files.

/ 100

- ◆ The Pascal *type system* is more expressive than the Algol 60 one (repairing some of its loopholes), and simpler and more limited than the Algol 68 one (eliminating some of the compilation difficulties).

A restriction that made Pascal simpler than Algol 68:

```
procedure Allowed( j,k: integer );
procedure AlsoAllowed( procedure P(i:integer);
                      j,k: integer );

procedure
NotAllowed( procedure MyProc( procedure P(i:integer) ) );
```

/ 101

- ◆ Pascal uses a mixture of *name* and *structural* equivalence for determining if two variables have the same type.

Name equivalence is used in most cases for determining if formal and actual parameters in subprogram calls have the same type; structural equivalence is used in most other situations.

- ◆ Parameters are passed by value or reference.

Complete static type checking is possible for correspondence of actual and formal parameter types in each subprogram call.

/ 103

- ◆ Pascal was the first language to propose index checking.
- ◆ Problematically, in Pascal, the index type of an array is part of its type. The Pascal standard defines *conformant array parameters* whose bounds are implicitly passed to a procedure. The Ada programming language uses so-called *unconstrained array types* to solve this problem.

The subscript range must be fixed at compile time permitting the compiler to perform all address calculations during compilation.

```
procedure
  Allowed( a: array [1..10] of integer ) ;
procedure
  NotAllowed( n: integer; a: array [1..n] of integer ) ;
```

/ 102

Pascal variant records

Variant records have a part common to all records of that type, and a variable part, specific to some subset of the records.

```
type
  kind = ( unary, binary ) ;
type
  UBtree = record
    value: integer ;
    case k: kind of
      unary: ^UBtree ;
      binary: record
        left: ^UBtree ;
        right: ^UBtree
      end
    end
  end ;
```

/ 104

Variant records introduce *weaknesses* into the type system for a language.

1. Compilers do not usually check that the value in the tag field is consistent with the state of the record.
2. Tag fields are optional. If omitted, no checking is possible at run time to determine which variant is present when a selection is made of a field in a variant.

/ 105

Topic V

Object-oriented languages: Concepts and origins SIMULA and Smalltalk

References:

- ★ **Chapters 10 and 11** of *Concepts in programming languages* by J. C. Mitchell. CUP, 2003.
- ◆ **Chapters 8, and 12 (§§2 and 3)** of *Programming languages: Design and implementation* (3RD EDITION) by T. W. Pratt and M. V. Zelkowitz. Prentice Hall, 1999.

/ 107

Summary

- ◆ The Algol family of languages established the command-oriented syntax, with blocks, local declarations, and recursive functions, that are used in most current programming languages.
- ◆ The Algol family of languages is statically typed, as each expression has a type that is determined by its syntactic form and the compiler checks before running the program to make sure that the types of operations and operands agree.

/ 106

- ◆ **Chapter 7** of *Programming languages: Concepts & constructs* by R. Sethi (2ND EDITION). Addison-Wesley, 1996.
- ◆ **Chapters 14 and 15** of *Understanding programming languages* by M Ben-Ari. Wiley, 1996.
- ★ B. Stroustrup. What is “Object-Oriented Programming”? (1991 revised version). Proc. 1st European Conf. on Object-Oriented Programming. (Available on-line from <http://public.research.att.com/~bs/papers.html>.)

/ 108

Objects in ML !?

```
exception Empty ;
fun newStack(x0)
  = let val stack = ref [x0]
      in ref{ push = fn(x)
              => stack := ( x :: !stack )      ,
            pop = fn()
              => case !stack of
                  nil => raise Empty
                | h::t => ( stack := t; h )
            }end ;
exception Empty
val newStack = fn :
  'a -> {pop:unit -> 'a, push:'a -> unit} ref
```

/ 109

```
IntStack0 := !IntStack1 ;
val it = () : unit
#pop(!IntStack0)() ;
val it = 1 : int
#push(!IntStack0)(4) ;
val it = () : unit
```

/ 111

```
val BoolStack = newStack(true) ;
val BoolStack = ref {pop=fn,push=fn}
  : {pop:unit -> bool, push:bool -> unit} ref
val IntStack0 = newStack(0) ;
val IntStack0 = ref {pop=fn,push=fn}
  : {pop:unit -> int, push:int -> unit} ref
val IntStack1 = newStack(1) ;
val IntStack1 = ref {pop=fn,push=fn}
  : {pop:unit -> int, push:int -> unit} ref
```

/ 110

```
map ( #push(!IntStack0) ) [3,2,1] ;
val it = [(),(),()] : unit list
map ( #pop(!IntStack0) ) [(),(),(),()] ;
val it = [1,2,3,4] : int list
```

NB:

- ◆ The *stack discipline* for activation records fails!
- ◆ Is ML an object-oriented language?
 - Of course not!
 - Why?

/ 112

Basic concepts in object-oriented languages^a

Four main **language concepts** for object-oriented languages:

1. Dynamic lookup.
2. Abstraction.
3. Subtyping.
4. Inheritance.

^aNotes from **Chapter 10** of *Concepts in programming languages* by J. C. Mitchell. CUP, 2003.

/ 113

- ◆ Dynamic lookup is sometimes confused with **overloading**, which is a mechanism based on *static types* of operands. However, the two are very different. **?** Why?

There is a family of object-oriented languages that is based on the *“run-time overloading”* view of dynamic lookup. The most prominent design of this form is CLOS (= Common Lisp Object System), which features *multiple dispatch*.

/ 115

Dynamic lookup

- ◆ **Dynamic lookup** means that when a message is sent to an object, the method to be executed is selected dynamically, at **run time**, according to the implementation of the object that receives the message. In other words, the object “chooses” how to respond to a message.
The important property of dynamic lookup is that different objects may implement the same operation differently, and so may respond to the same message in different ways.

/ 114

Abstraction

- ◆ **Abstraction** means that implementation details are hidden inside a program unit with a specific interface. For objects, the interface usually consists of a set of methods that manipulate hidden data.
- ◆ Abstraction based on **objects** is similar in many ways to abstraction based on **abstract data types**: Objects and abstract data types both combine functions and data, and abstraction in both cases involves distinguishing between a public interface and private implementation.
Other features of object-oriented languages, however, make abstraction in object-oriented languages more flexible than abstraction with abstract data types.

/ 116

Subtyping

- ◆ *Subtyping* is a relation on types that allows values of one type to be used in place of values of another. Specifically, if an object *a* has all the functionality of another object *b*, then we may use *a* in any context expecting *b*.
- ◆ The basic principle associated with subtyping is *substitutivity*: If *A* is a subtype of *B*, then any expression of type *A* may be used without type error in any context that requires an expression of type *B*.

/ 117

Inheritance

- ◆ *Inheritance* is the ability to reuse the definition of one kind of object to define another kind of object.
- ◆ The importance of inheritance is that it saves the effort of duplicating (or reading duplicated) code and that, when one class is implemented by inheriting from another, changes to one affect the other. This has a significant impact on code maintenance and modification.

/ 119

- ◆ The primary advantage of subtyping is that it permits uniform operations over various types of data.
For instance, subtyping makes it possible to have heterogeneous data structures that contain objects that belong to different subtypes of some common type.
- ◆ Subtyping in an object-oriented language allows functionality to be added without modifying general parts of a system.

/ 118

Inheritance is not subtyping^a

Subtyping is a relation on interfaces,
inheritance is a relation on implementations.

One reason subtyping and inheritance are often confused is that some class mechanisms combine the two. A typical example is C++, in which *A* will be recognized by the compiler as a subtype of *B* only if *B* is a public base class of *A*. Combining subtyping and inheritance is an elective design decision.

^aInterested students may consult the POPL'90 paper *Inheritance is not subtyping* by W. R. Cook, W. L. Hill and P. S. Canning available on-line from <http://www.cs.utexas.edu/users/wcook/publications.htm>.

/ 120

History of objects

SIMULA and Smalltalk

- ◆ Objects were invented in the design of **SIMULA** and refined in the evolution of **Smalltalk**.
- ◆ **SIMULA: The first object-oriented language.**
The object model in SIMULA was based on procedures activation records, with objects originally described as procedures that return a pointer to their own activation record.
- ◆ **Smalltalk: A dynamically typed object-oriented language.**
Many object-oriented ideas originated or were popularised by the Smalltalk group, which built on Alan Kay's then-futuristic idea of the Dynabook.

/ 121

- ◆ A generic event-based simulation program

```
Q := make_queue(initial_event);
repeat
  select event e from Q
  simulate event e
  place all events generated by e on Q
until Q is empty
```

naturally requires:

- ◆ A data structure that may contain a variety of kinds of events. \rightsquigarrow subtyping
- ◆ The selection of the simulation operation according to the kind of event being processed. \rightsquigarrow dynamic lookup
- ◆ Ways in which to structure the implementation of related kinds of events. \rightsquigarrow inheritance

/ 123

SIMULA

- ◆ Extremely influential as the first language with classes objects, dynamic lookup, subtyping, and inheritance.
- ◆ Originally designed for the purpose of *simulation* by O.-J. Dahl and K. Nygaard at the Norwegian Computing Center, Oslo, in the 1960s.
- ◆ SIMULA was designed as an extension and modification of Algol 60. The main features added to Algol 60 were: class concepts and reference variables (pointers to objects); pass-by-reference; input-output features; coroutines (a mechanism for writing concurrent programs).

/ 122

Objects in SIMULA

Class: A procedure returning a pointer to its activation record.

Object: An activation record produced by call to a class, called an instance of the class. \rightsquigarrow a SIMULA object is a closure

- ◆ SIMULA implementations place objects on the heap.
- ◆ Objects are deallocated by the garbage collector (which deallocates objects only when they are no longer reachable from the program that created them).

/ 124

SIMULA

Object-oriented features

- ◆ *Objects*: A SIMULA object is an activation record produced by call to a class.
- ◆ *Classes*: A SIMULA class is a procedure that returns a pointer to its activation record. The body of a class may initialise the objects it creates.
- ◆ *Dynamic lookup*: Operations on an object are selected from the activation record of that object.

/ 125

SIMULA 67 did not distinguish between public and private members of classes.

A later version of the language, however, allowed attributes to be made “protected”, which means that they are accessible for subclasses (but not for other classes), or “hidden”, in which case they are not accessible to subclasses either.

/ 127

- ◆ *Abstraction*: Hiding was not provided in SIMULA 67 but was added later and used as the basis for C++.
- ◆ *Subtyping*: Objects are typed according to the classes that create them. Subtyping is determined by class hierarchy.
- ◆ *Inheritance*: A SIMULA class may be defined, by class prefixing, as an extension of a class that has already been defined including the ability to redefine parts of a class in a subclass.

/ 126

SIMULA

Further object-related features

- ◆ *Inner*, which indicates that the method of a subclass should be called in combination with execution of superclass code that contains the `inner` keyword.
- ◆ *Inspect* and *qua*, which provide the ability to test the type of an object at run time and to execute appropriate code accordingly. (`inspect` is a class (type) test, and `qua` is a form of type cast that is checked for correctness at run time.)

/ 128

SIMULA

Sample code^a

```
CLASS POINT(X,Y); REAL X, Y;
  COMMENT***CARTESIAN REPRESENTATION
BEGIN
  BOOLEAN PROCEDURE EQUALS(P); REF(POINT) P;
  IF P /= NONE THEN
    EQUALS := ABS(X-P.X) + ABS(Y-P.Y) < 0.00001;
  REAL PROCEDURE DISTANCE(P); REF(POINT) P;
  IF P == NONE THEN ERROR ELSE
    DISTANCE := SQRT( (X-P.X)**2 + (Y-P.Y)**2 );
END***POINT***
```

^aSee Chapter 4(§1) of *SIMULA begin* (2ND EDITION) by G. Birtwistle, O.-J. Dahl, B. Myhrhug, and K. Nygaard. Chartwell-Bratt Ltd., 1980.

/ 129

```
COMMENT*** INITIALISATION CODE
REAL D;
D := SQRT( A**2 + B**2 )
IF D = 0.0 THEN ERROR ELSE
  BEGIN
    D := 1/D;
    A := A*D; B := B*D; C := C * D;
  END;
END***LINE***
```

/ 131

```
CLASS LINE(A,B,C); REAL A,B,C;
  COMMENT***Ax+By+C=0 REPRESENTATION
BEGIN
  BOOLEAN PROCEDURE PARALLELTO(L); REF(LINE) L;
  IF L /= NONE THEN
    PARALLELTO := ABS( A*L.B - B*L.A ) < 0.00001;
  REF(POINT) PROCEDURE MEETS(L); REF(LINE) L;
  BEGIN REAL T;
  IF L /= NONE and ~PARALLELTO(L) THEN
    BEGIN
      ...
      MEETS := NEW POINT(..., ...);
    END;
  END;***MEETS***
```

/ 130

SIMULA

Subclasses and inheritance

SIMULA syntax for a class **C1** with subclasses **C2** and **C3** is

```
CLASS C1
  <DECLARATIONS1>;
C1 CLASS C2
  <DECLARATIONS2>;
C1 CLASS C3
  <DECLARATIONS3>;
```

When we create a **C2** object, for example, we do this by first creating a **C1** object (activation record) and then appending a **C2** object (activation record).

/ 132

SIMULA

Object types and subtypes

Example:

```
POINT CLASS COLOREDPOINT(C); COLOR C;
BEGIN
  BOOLEAN PROCEDURE EQUALS(Q); REF(COLOREDPOINT) Q;
  ...;
END**COLOREDPOINT**

REF(POINT) P; P := NEW POINT(1.0,2.5);
REF(COLOREDPOINT) CP; CP := NEW COLOREDPOINT(2.5,1.0,RED);
```

NB: SIMULA 67 did not hide fields. Thus,

```
CP.C := BLUE;
```

changes the color of the point referenced by CP.

/ 133

- ◆ All instances of a class are given the same *type*. The name of this type is the same as the name of the class.
- ◆ The class names (types of objects) are arranged in a *subtype* hierarchy corresponding exactly to the subclass hierarchy.

Examples:

1. CLASS A; A CLASS B;


```
REF(A) a; REF(B) b;
a := b; COMMENT***legal since B is a subclass of A
...
```

/ 134

that, if $B <: A$ then $REF(B) <: REF(A)$.

This code ...

```
PROCEDURE ASSIGNa( REF(A) x )
  BEGIN x := a END;
ASSIGNa(b);
```

... will statically type check, but may cause a type error at run time.

P.S. The same type error occurs in the original implementation of Eiffel.^a

^aInterested students may consult *A proposal for making Eiffel type-safe* by W. Cook in *The Computer Journal*, 32(4):305-311, 1989. Available on-line from <http://www.cs.utexas.edu/users/wcook/publications.htm>.

/ 135

/ 136

```
b := a; COMMENT***also legal, but checked at run
***time to make sure that a points
***to a B object, so as to avoid a
***type error
```

2. inspect a

```
when B do b := a
otherwise ...
```

3. An error in the original SIMULA type checker surrounding the relationship between subtyping and inheritance:

```
CLASS A; A CLASS B;
```

SIMULA subclassing produces the subtype relation $B <: A$.

```
REF(A) a; REF(B) b;
```

SIMULA also uses the semantically incorrect principle

Smalltalk

- ◆ Developed at XEROX PARC in the 1970s.
- ◆ Major language that popularised objects; very flexible and powerful.
- ◆ The object metaphor was extended and refined.
 - ◆ Used some ideas from SIMULA; but it was a completely new language, with new terminology and an original syntax.
 - ◆ Abstraction via private *instance variables* (data associated with an object) and public *methods* (code for performing operations).
 - ◆ Everything is an object; even a class. All operations are messages to objects.

/ 137

Smalltalk Terminology

- ◆ **Object**: A combination of private data and functions. Each object is an *instance* of some class.
- ◆ **Class**: A template defining the implementation of a set of objects.
- ◆ **Subclass**: Class defined by inheriting from its superclass.
- ◆ **Selector**: The name of a message (analogous to a function name).
- ◆ **Message**: A selector together with actual parameter values (analogous to a function call).
- ◆ **Method**: The code in a class for responding to a message.
- ◆ **Instance variable**: Data stored in an individual object (instance class).

/ 139

Smalltalk

Motivating application: Dynabook

- ◆ Concept developed by Alan Kay.
- ◆ Influence on Smalltalk:
 - ◆ Objects and classes as useful organising concepts for building an entire programming environment and system.
 - ◆ Language intended to be the operating system interface as well as the programming language for Dynabook.
 - ◆ Syntax designed to be used with a special-purpose editor.
 - ◆ The implementation emphasised flexibility and ease of use over efficiency.

/ 138

Smalltalk Classes and objects

class name	Point
super class	Object
class var	pi
instance var	x, y
class messages and methods	
⟨... names and codes for methods ...⟩	
instance messages and methods	
⟨... names and codes for methods ...⟩	

Definition of Point class

/ 140

A class message and method for point objects

```
newX:xvalue Y:yvalue ||  
  ^ self new x: xvalue y: yvalue
```

A new point at coordinates (3,4) is created when the message

```
newX:3 Y:4
```

is sent to the Point class.

For instance:

```
p <- Point newX:3 Y:4
```

Some instance messages and methods

```
x || ^x  
y || ^y  
moveDx: dx Dy: dy ||  
  x <- x+dx  
  y <- y+dy
```

Executing the following code

```
p moveDX:2 Y:1
```

the value of the expressions `p x` and `p y` is the object 5.

/ 141

/ 142

Smalltalk Inheritance

class name	ColoredPoint
super class	Point
class var	
instance var	color
class messages and methods	
newX:xv Y:yv C:cv	<...code ...>
instance messages and methods	
color	^color
draw	<...code ...>

Definition of ColoredPoint class

- ◆ `ColoredPoint` inherits instance variables `x` and `y`, methods `x`, `y`, `moveDX:Dy:`, *etc.*
- ◆ `ColoredPoint` adds an instance variable `color` and a method `color` to return the `color` of a `ColoredPoint`.
- ◆ The `ColoredPoint draw` method *redefines* (or *overrides*) the one inherited from `Point`.
- ◆ An option available in Smalltalk is to specify that a superclass method should be undefined on a subclass.

/ 143

/ 144

Smalltalk

Abstraction

Example: Consider

```
newX:xv Y:yv C:cv ||
  ^ self new x:xv y:yv color:cv
cp <- ColoredPoint newX:1 Y:2 C:red
cp moveDx:3 Dy:4
```

The value of `cp x` is the object `4`, and the value of the expression `cp color` is the object `red`.

Note that even though `moveDx:Dy:` is an inherited method, defined originally for points without color, the result of moving a `ColoredPoint` is again a `ColoredPoint`.

/ 145

Smalltalk

Dynamic lookup

The run-time structures used for Smalltalk classes and objects support *dynamic lookup* in two ways.

1. Methods are selected through the receiver object.
2. Method lookup starts with the method dictionary of the class of the receiver and then proceeds upwards through the class hierarchy.

/ 147

Smalltalk rules:

- ◆ *Methods are public.*
Any code with a pointer to an object may send any message to that object. If the corresponding method is defined in the class of the object, or any superclass, the method will be invoked. This makes all methods of an object visible to any code that can access the object.
- ◆ *Instance variables are protected.*
The instance variables of an object are accessible only to methods of the class of the object and to methods of its subclasses.

/ 146

Smalltalk

Self and super

- ◆ The special symbol `self` may be used in the body of a Smalltalk method. The special property of `self` is that it always refers to the object that contains this method, whether directly or by inheritance.
- ◆ The special symbol `super` is similar to `self`, except that, when a message is sent to `super`, the search for the appropriate method body starts with the superclass of the object instead of the class of the object. This mechanism provides a way of accessing a superclass version of a method that has been overridden in the subclass.

/ 148

Smalltalk

Interfaces as object types

Although Smalltalk does not use any static type checking, there is an implicit form of type that every Smalltalk programmer uses in some way.


The *type* of an object in Smalltalk is its interface, *i.e.* the set of messages that can be sent to the object without receiving the error “message not understood”.

The interface of an object is determined by its class, as a class lists the messages that each object will answer. However, different classes may implement the same messages, as there are no Smalltalk rules to keep different classes from using the same selector names.

Example: A factorial method

```
factorial ||
  self <= 1
    ifTrue: [^1]
    ifFalse: [^ (self-1) factorial * self]
```

in the `Integer` class for



/ 149

/ 150

Smalltalk Subtyping

Type *A* is a *subtype* of type *B* if any context expecting an expression of type *B* may take any expression of type *A* without introducing a type error.

Semantically, in Smalltalk, it makes sense to associate *subtyping* with the *superset* relation on class interfaces.

? Why?

- ◆ In Smalltalk, the interface of a subclass is often a subtype of the interface of its superclass. The reason being that a subclass will ordinarily inherit all of the methods of its superclass, possibly adding more methods.
- ◆ In general, however, subclassing does not always lead to subtyping in Smalltalk.
 1. Because it is possible to delete a method from a superclass in a subclass, a subclass may not produce a subtype.
 2. On the other hand, it is easy to have subtyping without inheritance.

/ 151

/ 152

Smalltalk

Object-oriented features

- ◆ **Objects:** A Smalltalk object is created by a class.
At run time, an object stores its instance variables and a pointer to the instantiating class.
- ◆ **Classes:** A Smalltalk class defines variables, class methods, and the instance methods that are shared by all objects of the class.
At run time, the class data structure contains pointers to an instance variable template, a method dictionary, and the superclass.

/ 153

Topic VI

Types in programming languages

References:

- ◆ **Chapter 6** of *Concepts in programming languages* by J. C. Mitchell. CUP, 2003.
- ◆ **Sections 4.9 and 8.6** of *Programming languages: Concepts & constructs* by R. Sethi (2ND EDITION). Addison-Wesley, 1996.

/ 155

- ◆ **Abstraction:** Abstraction is provided through protected instance variables. All methods are public but instance variables may be accessed only by the methods of the class and methods of subclasses.
- ◆ **Subtyping:** Smalltalk does not have a compile-time type system. Subtyping arises implicitly through relations between the interfaces of objects. Subtyping depends on the set of messages that are understood by an object, not the representation of objects or whether inheritance is used.
- ◆ **Inheritance:** Smalltalk subclasses inherit all instance variables and methods of their superclasses. Methods defined in a superclass may be redefined in a subclass or deleted.

/ 154

Types in programming

- ◆ A **type** is a collection of computational entities that share some common property.
- ◆ There are three main uses of types in programming languages:
 1. naming and organizing concepts,
 2. making sure that bit sequences in computer memory are interpreted consistently,
 3. providing information to the compiler about data manipulated by the program.

/ 156

- ◆ Using types to organise a program makes it easier for someone to read, understand, and maintain the program. Types can serve an important purpose in documenting the design and intent of the program.
- ◆ Type information in programs can be used for many kinds of optimisations.

/ 157

Type safety

A programming language is *type safe* if no program is allowed to violate its type distinctions.

Safety	Example language	Explanation
Not safe	C, C++	Type casts, pointer arithmetic
Almost safe	Pascal	Explicit deallocation; dangling pointers
Safe	LISP, SML, Smalltalk, Java	Type checking

/ 159

Type systems

A *type system* for a language is a set of rules for associating a type with phrases in the language.

Terms strong and weak refer to the effectiveness with which a type system prevents errors. A type system is *strong* if it accepts only *safe* phrases. In other words, phrases that are accepted by a strong type system are guaranteed to evaluate without type error. A type system is *weak* if it is not strong.

/ 158

Type checking

A *type error* occurs when a computational entity is used in a manner that is inconsistent with the concept it represents. *Type checking* is used to prevent some or all type errors, ensuring that the operations in a program are applied properly.

Some questions to be asked about type checking in a language:

- ◆ Is the type system *strong* or *weak*?
- ◆ Is the checking done *statically* or *dynamically*?
- ◆ How *expressive* is the type system; that is, amongst safe programs, how many does it accept?

/ 160

Static and dynamic type checking

Run-time type checking: The compiler generates code so that, when an operation is performed, the code checks to make sure that the operands have the correct types.

Examples: LISP, Smalltalk.

Compile-time type checking: The compiler checks the program text for potential type errors.

Example: SML.

NB: Most programming languages use some combination of compile-time and run-time type checking.

/ 161

Type equality

The question of *type equality* arises during type checking.

? What does it mean for two types to be equal!?

Structural equality. Two type expressions are *structurally equal* if and only if they are equivalent under the following three rules.

- SE1.** A type name is structurally equal to itself.
- SE2.** Two types are structurally equal if they are formed by applying the same type constructor to structurally equal types.
- SE3.** After a type declaration, say `type n = T`, the type name `n` is structurally equal to `T`.

/ 163

Static vs. dynamic type checking

Main trade-offs between compile-time and run-time checking:

Form of type checking	Advantages	Disadvantages
Run-time	Prevents type errors	Slows program execution
Compile-time	Prevents type errors Eliminates run-time tests Finds type errors before execution and run-time tests	May restrict programming because tests are <i>conservative</i>

/ 162

Name equality. Pure name equality. A type name is equal to itself, but no constructed type is equal to any other constructed type.

Transitive name equality. A type name is equal to itself and can be declared equal to other type names.

Type-expression equality. A type name is equal only to itself. Two type expressions are equal if they are formed by applying the same constructor to equal expressions. In other words, the expressions have to be identical.

/ 164

Examples:

- ◆ **Type equality in Pascal/Modula-2.** Type equality was left ambiguous in Pascal. Its successor, Modula-2, avoided ambiguity by defining two types to be *compatible* if
 1. they are the same name, or
 2. they are s and t , and $s = t$ is a type declaration, or
 3. one is a subrange of the other, or
 4. both are subranges of the same basic type.
- ◆ **Type equality in C/C++.** C uses structural equivalence for all types except for records (*structs*). *struct* types are named in C and C++ and the name is treated as a type, equal only to itself. This constraint saves C from having to deal with recursive types.

/ 165

Type inference

- ◆ *Type inference* is the process of determining the types of phrases based on the constructs that appear in them.
- ◆ An important language innovation.
- ◆ A cool algorithm.
- ◆ Gives some idea of how other static analysis algorithms work.

/ 167

Type declarations

There are two basic forms of type declarations:

Transparent. An alternative name is given to a type that can also be expressed without this name.

Opaque. A new type is introduced into the program that is not equal to any other type.

/ 166

Polymorphism

Polymorphism, which literally means “having multiple forms”, refers to constructs that can take on different types as needed.

Forms of polymorphism in contemporary programming languages:

Parametric polymorphism. A function may be applied to any arguments whose types match a type expression involving type variables.

Parametric polymorphism may be:

Implicit. Programs do not need to contain types; types and instantiations of type variables are computed.

Example: SML.

/ 168

Explicit. The program text contains type variables that determine the way that a construct may be treated polymorphically.

Explicit polymorphism often involves explicit instantiation or type application to indicate how type variables are replaced with specific types in the use of a polymorphic construct.

Example: C++ templates.

Ad hoc polymorphism or overloading. Two or more implementations with different types are referred to by the same name.

Subtype polymorphism. The subtype relation between types allows an expression to have many possible types.

/ 169

When a *polymorphic exception* is declared, SML ensures that it is used with only one type. The type of a top level exception must be monomorphic and the type variables of a local exception are frozen.

Consider the following nonsense:

```
exception Poly of 'a ; (** ILLEGAL!!! **)
(raise Poly true) handle Poly x => x+1 ;
```

/ 171

Polymorphic exceptions

Example: Depth-first search for finitely-branching trees.

```
datatype
  'a FBtree = node of 'a * 'a FBtree list ;
fun dfs P (t: 'a FBtree)
  = let
    exception Ok of 'a;
    fun auxdfs( node(n,F) )
      = if P n then raise Ok n
        else foldl (fn(t,_) => auxdfs t) NONE F ;
  in
    auxdfs t handle Ok n => SOME n
  end ;
val dfs = fn : ('a -> bool) -> 'a FBtree -> 'a option
```

/ 170

Topic VII

Data abstraction and modularity SML Modules^a

References:

- ◆ **Chapter 7** of *ML for the working programmer* (2ND EDITION) by L. C. Paulson. CUP, 1996.

^aLargely based on an *Introduction to SML Modules* by Claudio Russo (<http://research.microsoft.com/~crusso>).

/ 172

- ◆ *The Standard ML Basis Library* edited by E. R. Gansner and J. H. Reppy. CUP, 2004.

[A useful introduction to SML standard libraries, and a good example of modular programming.]

- ◆ <http://www.standardml.org/>

/ 173

The Modules language

Writing a real program as an unstructured sequence of Core definitions quickly becomes unmanageable.

```
type nat = int
val zero = 0
fun succ x = x + 1
fun iter b f i =
  if i = zero then b
    else f (iter b f (i-1))
...
(* thousands of lines later *)
fun even (n:nat) = iter true not n
```

The SML Modules language lets one split large programs into separate units with descriptive interfaces.

/ 175

The Core and Modules languages

SML consists of two sub-languages:

- ◆ The *Core* language is for *programming in the small*, by supporting the definition of types and expressions denoting values of those types.
- ◆ The *Modules* language is for *programming in the large*, by grouping related Core definitions of types and expressions into self-contained units, with descriptive interfaces.

The *Core* expresses details of *data structures* and *algorithms*. The *Modules* language expresses *software architecture*. Both languages are largely independent.

/ 174

SML Modules Signatures and structures

- ◆ An *abstract data type* is a type equipped with a set of operations, which are the only operations applicable to that type.
Its representation can be changed without affecting the rest of the program.
- ◆ *Structures* let us *package* up declarations of related types, values, and functions.
- ◆ *Signatures* let us *specify* what components a structure must contain.

/ 176

Structures

In Modules, one can encapsulate a sequence of Core type and value definitions into a unit called a *structure*.

We enclose the definitions in between the keywords

```
struct ... end.
```

Example: A structure representing the natural numbers, as positive integers.

```
struct
  type nat = int
  val zero = 0
  fun succ x = x + 1
  fun iter b f i = if i = zero then b
                  else f (iter b f (i-1))
end
```

/ 177

Nested structures

Structures can be nested inside other structures, in a hierarchy.

```
structure IntNatAdd =
  struct
    structure Nat = IntNat
    fun add n m = Nat.iter m Nat.succ n
  end
  ...
fun mult n m =
  IntNatAdd.Nat.iter IntNatAdd.Nat.zero (IntNatAdd.add m) n
```

The dot notation (`IntNatAdd.Nat`) accesses a nested structure.

Sequencing dots provides deeper access (`IntNatAdd.Nat.zero`).

Nesting and dot notation provides *name-space* control.

/ 179

The dot notation

One can name a structure by binding it to an identifier.

```
structure IntNat =
  struct
    type nat = int
    ...
    fun iter b f i = ...
  end
```

Components of a structure are accessed with the *dot notation*.

```
fun even (n: IntNat.nat) = IntNat.iter true not n
```

NB: Type `IntNat.nat` is statically equal to `int`.

Value `IntNat.iter` dynamically evaluates to a closure.

/ 178

Concrete signatures

Signature expressions specify the types of structures by listing the specifications of their components.

A signature expression consists of a *sequence* of component specifications, enclosed in between the keywords `sig ... end`.

```
sig type nat = int
  val zero : nat
  val succ : nat -> nat
  val 'a iter : 'a -> ('a->'a) -> nat -> 'a
end
```

This signature fully describes the *type* of `IntNat`.

The specification of type `nat` is *concrete*: it must be `int`.

/ 180

Opaque signatures

On the other hand, the following signature

```
sig type nat
  val zero : nat
  val succ : nat -> nat
  val 'a iter : 'a -> ('a->'a) -> nat -> 'a
end
```

specifies structures that are free to use *any* implementation for type `nat` (perhaps `int`, or `word`, or some recursive datatype).

This specification of type `nat` is *opaque*.

Example: Polymorphic functional stacks.

```
signature STACK =
sig
  exception E
  type 'a reptype (* <-- INTERNAL REPRESENTATION *)
  val new: 'a reptype
  val push: 'a -> 'a reptype -> 'a reptype
  val pop: 'a reptype -> 'a reptype
  val top: 'a reptype -> 'a
end ;
```

```
structure MyStack: STACK =
struct
  exception E ;
  type 'a reptype = 'a list ;
  val new = [] ;
  fun push x s = x::s ;
  fun split( h::t ) = ( h , t )
    | split _ = raise E ;
  fun pop s = #2( split s ) ;
  fun top s = #1( split s ) ;
end ;
```

```
val MyEmptyStack = MyStack.new ;
val MyStack0 = MyStack.push 0 MyEmptyStack ;
val MyStack01 = MyStack.push 1 MyStack0 ;
val MyStack0' = MyStack.pop MyStack01 ;
MyStack.top MyStack0' ;

val MyEmptyStack = [] : 'a MyStack.reptype
val MyStack0 = [0] : int MyStack.reptype
val MyStack01 = [1,0] : int MyStack.reptype
val MyStack0' = [0] : int MyStack.reptype
val it = 0 : int
```

Named and nested signatures

Signatures may be *named* and referenced, to avoid repetition:

```
signature NAT =
  sig type nat
      val zero : nat
      val succ : nat -> nat
      val 'a iter : 'a -> ('a->'a) -> nat -> 'a
  end
```

Nested signatures specify named sub-structures:

```
signature Add =
  sig structure Nat: NAT (* references NAT *)
      val add: Nat.nat -> Nat.nat -> Nat.nat
  end
```

/ 185

Signature matching

Q: When does a structure satisfy a signature?

A: The type of a structure *matches* a signature whenever it implements at least the components of the signature.

- The structure must *realise* (i.e. define) all of the opaque type components in the signature.
- The structure must *enrich* this realised signature, component-wise:
 - ★ every concrete type must be implemented equivalently;
 - ★ every specified value must have a more general type scheme;
 - ★ every specified structure must be enriched by a substructure.

/ 187

Signature inclusion

To avoid nesting, one can also directly *include* a signature identifier:

```
sig include NAT
  val add: nat -> nat -> nat
end
```

NB: This is equivalent to the following signature.

```
sig type nat
  val zero: nat
  val succ: nat -> nat
  val 'a iter: 'a -> ('a->'a) -> nat -> 'a
  val add: nat -> nat -> nat
end
```

/ 186

Properties of signature matching

The components of a structure can be defined in a different order than in the signature; names matter but ordering does not.

A structure may contain more components, or components of more general types, than are specified in a matching signature.

Signature matching is *structural*. A structure can match many signatures and there is no need to pre-declare its matching signatures (unlike “interfaces” in Java and C#).

Although similar to record types, signatures actually play a number of different roles.

/ 188

Subtyping

Signature matching supports a form of *subtyping* not found in the Core language:

- ◆ A structure with more type, value, and structure components may be used where fewer components are expected.
- ◆ A value component may have a more general type scheme than expected.

/ 189

Transparency of `_: _`

Although the `_: _` operator can hide names, it does not conceal the definitions of opaque types.

Thus, the fact that `ResIntNat.nat = IntNat.nat = int` remains *transparent*.

For instance the application `ResIntNat.succ(~3)` is still well-typed, because `~3` has type `int` ... but `~3` is negative, so not a valid representation of a natural number!

/ 191

Using signatures to restrict access

The following structure uses a *signature constraint* to provide a restricted view of `IntNat`:

```
structure ResIntNat =  
  IntNat : sig type nat  
            val succ : nat->nat  
            val iter : nat->(nat->nat)->nat->nat  
          end
```

NB: The constraint `str:sig` prunes the structure `str` according to the signature `sig`:

- ◆ `ResIntNat.zero` is *undefined*;
- ◆ `ResIntNat.iter` is *less* polymorphic than `IntNat.iter`.

/ 190

SML Modules Information hiding

In SML, we can limit outside access to the components of a structure by *constraining* its signature in *transparent* or *opaque* manners.

Further, we can *hide* the representation of a type by means of an *abstype* declaration.

The combination of these methods yields *abstract structures*.

/ 192

Using signatures to hide types identities

With different syntax, signature matching can also be used to enforce *data abstraction*:

```
structure AbsNat =
  IntNat :> sig type nat
              val zero: nat
              val succ: nat->nat
              val 'a iter: 'a->('a->'a)->nat->'a
            end
```

The constraint `str :> sig` prunes `str` but also generates a new, *abstract* type for each opaque type in `sig`.

/ 193

Opaque signature constraints

```
structure MyOpaqueStack :> STACK = MyStack ;

val MyEmptyOpaqueStack = MyOpaqueStack.new ;
val MyOpaqueStack0 = MyOpaqueStack.push 0 MyEmptyOpaqueStack ;
val MyOpaqueStack01 = MyOpaqueStack.push 1 MyOpaqueStack0 ;
val MyOpaqueStack0' = MyOpaqueStack.pop MyOpaqueStack01 ;
MyOpaqueStack.top MyOpaqueStack0' ;

val MyEmptyOpaqueStack = - : 'a MyOpaqueStack.reptype
val MyOpaqueStack0 = - : int MyOpaqueStack.reptype
val MyOpaqueStack01 = - : int MyOpaqueStack.reptype
val MyOpaqueStack0' = - : int MyOpaqueStack.reptype
val it = 0 : int
```

/ 195

Now, the actual implementation of `AbsNat.nat` by `int` is *hidden*, so that `AbsNat.nat` \neq `int`.

`AbsNat` is just `IntNat`, but with a hidden type representation.

`AbsNat` defines an *abstract datatype* of natural numbers: the only way to construct and use values of the abstract type `AbsNat.nat` is through the operations, `zero`, `succ`, and `iter`.

For example, the application `AbsNat.succ(~3)` is ill-typed: `~3` only has type `int`, not `AbsNat.nat`. This is what we want, since `~3` is not a natural number in our representation.

In general, abstractions can also prune and specialise components.

/ 194

abstypes

```
structure MyHiddenStack: STACK =
struct
  exception E ;
  abstype 'a reptype = S of 'a list (* <-- HIDDEN *)
  with (* REPRESENTATION *)
    val new = S [] ;
    fun push x (S s) = S( x::s ) ;
    fun pop( S [] ) = raise E
      | pop( S(_::t) ) = S( t ) ;
    fun top( S [] ) = raise E
      | top( S(h::_) ) = h ;
  end ;
end ;
```

/ 196

```

val MyHiddenEmptyStack = MyHiddenStack.new ;
val MyHiddenStack0 = MyHiddenStack.push 0 MyHiddenEmptyStack ;
val MyHiddenStack01 = MyHiddenStack.push 1 MyHiddenStack0 ;
val MyHiddenStack0' = MyHiddenStack.pop MyHiddenStack01 ;
MyHiddenStack.top MyHiddenStack0' ;

val MyHiddenEmptyStack = - : 'a MyHiddenStack.reptype
val MyHiddenStack0 = - : int MyHiddenStack.reptype
val MyHiddenStack01 = - : int MyHiddenStack.reptype
val MyHiddenStack0' = - : int MyHiddenStack.reptype
val it = 0 : int

```

/ 197

SML Modules

Functors

- ◆ An SML *functor* is a structure that takes other structures as parameters.
- ◆ Functors let us write program units that can be combined in different ways. Functors can also express generic algorithms.

/ 199

Datatype and exception specifications

Signatures can also specify datatypes and exceptions:

```

structure PredNat =
  struct
    datatype nat = zero | succ of nat
    fun iter b f i = ...
    exception Pred
    fun pred zero = raise Pred
      | pred (succ n) = n
  end
:> sig
  datatype nat = zero | succ of nat
  val iter: 'a->('a->'a)->(nat->'a)
  exception Pred
  val pred: nat -> nat (* raises Pred *)
end

```

This means that clients can still pattern match on datatype constructors, and handle exceptions.

/ 198

Functors

Modules also supports parameterised structures, called *functors*.

Example: The functor `AddFun` below takes any implementation, `N`, of naturals and re-exports it with an addition operation.

```

functor AddFun(N:NAT) =
  struct
    structure Nat = N
    fun add n m = Nat.iter n (Nat.succ) m
  end

```

/ 200

A functor is a *function* mapping a formal argument structure to a concrete result structure.

The body of a functor may assume no more information about its formal argument than is specified in its signature.

In particular, opaque types are treated as distinct type parameters.

Each actual argument can supply its own, independent implementation of opaque types.

Example: Generic imperative stacks.

```
signature STACK =
sig
  type itemtype
  val push: itemtype -> unit
  val pop: unit -> unit
  val top: unit -> itemtype
end ;
```

/ 201

/ 203

Functor application

A functor may be used to create a structure by *applying* it to an actual argument:

```
structure IntNatAdd = AddFun(IntNat)
structure AbsNatAdd = AddFun(AbsNat)
```

The actual argument must match the signature of the formal parameter—so it can provide more components, of more general types.

Above, `AddFun` is applied twice, but to arguments that differ in their implementation of type `nat` (`AbsNat.nat` \neq `IntNat.nat`).

/ 202

```
exception E ;
functor Stack( T: sig type atype end ) : STACK =
struct
  type itemtype = T.atype
  val stack = ref( []: itemtype list )
  fun push x
    = ( stack := x :: !stack )
  fun pop()
    = case !stack of [] => raise E
      | _::s => ( stack := s )
  fun top()
    = case !stack of [] => raise E
      | t::_ => t
end ;
```

/ 204

```

structure intStack
  = Stack(struct type atype = int end) ;

structure intStack : STACK

intStack.push(0) ;
intStack.top() ;
intStack.pop() ;
intStack.push(4) ;

val it = () : unit
val it = 0 : intStack.itemtype
val it = () : unit
val it = () : unit

```

/ 205

Why functors ?

Functors support:

Code reuse.

`AddFun` may be applied many times to different structures, reusing its body.

Code abstraction.

`AddFun` can be compiled before any argument is implemented.

Type abstraction.

`AddFun` can be applied to different types `N.nat`.

/ 207

```

map ( intStack.push ) [3,2,1] ;
map ( fn _ => let val top = intStack.top()
              in intStack.pop(); top end )
      [(),(),(),()] ;

val it = [(),(),()] : unit list
val it = [1,2,3,4] : intStack.itemtype list

```

/ 206

Are signatures types ?

The syntax of Modules suggests that signatures are just the types of structures ... but signatures can contain opaque types.

In general, signatures describe *families of structures*, indexed by the realisation of any opaque types.

The interpretation of a signature really depends on how it is used!

In functor parameters, opaque types introduce *polymorphism*; in signature constraints, opaque types introduce *abstract types*.

Since type components may be type constructors, not just types, this is really *higher-order* polymorphism and abstraction.

/ 208

Structures as records

Structures are like Core records, but can contain definitions of types as well as values.

What does it mean to project a type component from a structure, e.g. `IntNatAdd.Nat.nat`?

Does one needs to evaluate the application `AddFun(IntNat)` at *compile-time* to simplify `IntNatAdd.Nat.nat` to `int`?

No! Its sufficient to know the *compile-time* types of `AddFun` and `IntNat`, ensuring a *phase distinction* between compile-time and run-time.

/ 209

Generativity

The following functor almost defines an identity function, but *re-abstracts* its argument:

```
functor GenFun(N:NAT) = N :> NAT
```

Now, each application of `GenFun` generates a new abstract type: For instance, for

```
structure X = GenFun(IntNat)
structure Y = GenFun(IntNat)
```

the types `X.nat` and `Y.nat` are *incompatible*, even though `GenFun` was applied to the *same* argument.

Functor application is *generative*: abstract types from the body of a functor are replaced by fresh types at each application. This is consistent with inlining the body of a functor at applications.

/ 211

Type propagation through functors

Each functor application *propagates* the actual realisation of its argument's opaque type components.

Thus, for

```
structure IntNatAdd = AddFun(IntNat)
structure AbsNatAdd = AddFun(AbsNat)
```

the type `IntNatAdd.Nat.nat` is just another name for `int`, and `AbsNatAdd.Nat.nat` is just another name for `AbsNat.nat`.

Examples:

```
IntNatAdd.Nat.succ(0) ✓
IntNatAdd.Nat.succ(IntNat.Nat.zero) ✓
AbsNatAdd.Nat.succ(AbsNat.Nat.zero) ✓
AbsNatAdd.Nat.succ(0) ✗
AbsNatAdd.Nat.succ(IntNat.Nat.zero) ✗
```

/ 210

Why should functors be generative?

It is really a design choice. Often, the invariants of the body of a functor depend on both the types *and values* imported from the argument.

```
functor OrdSet(O:sig type elem
  val compare: (elem * elem) -> bool
end) = struct
  type set = O.elem list (* ordered list of elements *)
  val empty = []
  fun insert e [] = [e]
  | insert e1 (e2::s) = if O.compare(e1,e2)
    then if O.compare(e2,e1) then e2::s else e1::e2::s
    else e2::insert e1 s
end :> sig type set
  val empty: set
  val insert: O.elem -> set -> set
end
```

/ 212

For

```
structure S = OrdSet(struct type elem=int fun compare(i,j)= i <= j end)
structure R = OrdSet(struct type elem=int fun compare(i,j)= i >= j end)
```

we want $S.set \neq R.set$ because their representation invariants depend on the `compare` function: the set $\{1, 2, 3\}$ is $[1, 2, 3]$ in $S.set$, but $[3, 2, 1]$ in $R.set$.

Sharing specifications

Functors are often used to combine different argument structures.

Sometimes, these structure arguments need to communicate values of a *shared* type.

For instance, we might want to implement a sum-of-squares function $(n, m \mapsto n^2 + m^2)$ using separate structures for naturals with addition and multiplication ...

Why functors ?

- ◆ Functors let one decompose a large programming task into separate subtasks.
- ◆ The propagation of types through application lets one extend existing abstract data types with type-compatible operations.
- ◆ Generativity ensures that applications of the same functor to data types with the same representation, but different invariants, return distinct abstract types.

Sharing violations

```
functor SQ(structure AddNat: sig
  structure Nat: sig type nat end
  val add:Nat.nat -> Nat.nat -> Nat.nat
end
structure MultNat: sig
  structure Nat: sig type nat end
  val mult:Nat.nat -> Nat.nat -> Nat.nat
end) =
struct fun sumsquare n m
  = AddNat.add (MultNat.mult n n) (MultNat.mult m m)
end
```

The above piece of code is *ill-typed*: the types `AddNat.Nat.nat` and `MultNat.Nat.nat` are opaque, and thus different. The `add` function cannot consume the results of `mult`.

Sharing specifications

The fix is to declare the type sharing directly at the specification of `MultNat.Nat.nat`, using a concrete, not opaque, specification:

```
functor SQ(  
  structure AddNat:  
    sig structure Nat: sig type nat end  
      val add: Nat.nat -> Nat.nat -> Nat.nat  
    end  
  structure MultNat:  
    sig structure Nat: sig type nat = AddNat.Nat.nat end  
      val mult: Nat.nat -> Nat.nat -> Nat.nat  
    end) =  
struct fun sumsquare n m  
  = AddNat.add (MultNat.mult n n) (MultNat.mult m m) ✓  
end
```

/ 217

Limitations of modules

Modules is great for expressing programs with a complicated static architecture, but it's not perfect:

- ◆ Functors are *first-order*: unlike Core functions, a functor cannot be applied to, nor return, another functor.
- ◆ Structure and functors are *second-class* values, with very limited forms of computation (dot notation and functor application): modules cannot be constructed by algorithms or stored in data structures.
- ◆ Module definitions are *too sequential*: splitting mutually recursive types and values into separate modules is awkward.

/ 219

Sharing constraints

Alternatively, one can use a post-hoc *sharing specification* to identify opaque types.

```
functor SQ(  
  structure AddNat: sig structure Nat: sig type nat end  
    val add: Nat.nat -> Nat.nat -> Nat.nat  
  end  
  structure MultNat: sig structure Nat: sig type nat end  
    val mult: Nat.nat -> Nat.nat -> Nat.nat  
  end  
  sharing type MultNat.Nat.nat = AddNat.Nat.nat ) =  
struct fun sumsquare n m  
  = AddNat.add (MultNat.mult n n) (MultNat.mult m m) ✓  
end
```

/ 218

Topic VIII

The state of the art Scala

References:

- ◆ *Scala By Example* by M. Odersky. Programming Methods Laboratory, EPFL, 2008.
- ◆ *An overview of the Scala programming language* by M. Odersky *et al.* Technical Report LAMP-REPORT-2006-001, Second Edition, 2006.

/ 220

Scala (I)

◆ Scala has been developed from 2001 in the Programming Methods Laboratory at EPFL by a group lead by Martin Odersky. It was first released publicly in 2004, with a second version released in 2006.

◆ Scala is aimed at the construction of components and component systems.

One of the major design goals of Scala was that it should be flexible enough to act as a convenient host language for domain specific languages implemented by library modules.

◆ Scala has been designed to work well with Java and C#. Every Java class is seen in Scala as two entities, a class containing all dynamic members and a singleton object, containing all static members.

Scala classes and objects can also inherit from Java classes and implement Java interfaces. This makes it possible to use Scala code in a Java framework.

◆ Scala's influences: Beta, C#, FamilyJ, gbeta, Haskell, Java, Jiazzi, ML_≤, Moby, MultiJava, Nice, OCaml, Pizza, Sather, Smalltalk, SML, XQuery, *etc.*

/ 221

A procedural language !

```
def qsort( xs: Array[Int] ) {
  def swap(i: Int, j: Int) {
    val t = xs(i); xs(i) = xs(j); xs(j) = t
  }
  def sort(l: Int, r: Int) {
    val pivot = xs( (l+r)/2 ); var i = l; var j = r
    while ( i <= j ) {
      while ( lt( xs(i), pivot ) ) i += 1
      while ( lt( xs(j), pivot ) ) j -= 1
      if ( i <= j ) { swap(i,j); i += 1; j -= 1 }
    }
    if ( l < j ) sort(l,j)
    if ( j < r ) sort(i,r)
  }
  sort(0,xs.length-1)
}
```

/ 222

NB:

- ◆ Definitions start with a reserved word.
- ◆ Type declarations use the colon notation.
- ◆ Array selections are written in functional notation.
In fact, arrays in Scala inherit from functions.
- ◆ Block structure.

/ 223

/ 224

A declarative language !

```
def qsort[T]( xs: Array[T] )( lt: (T,T)=>Boolean ): Array[T]
= if ( xs.length <= 1 ) xs
  else {
    val pivot = xs( xs.length/2 )
    Array.concat( qsort( xs filter (x => lt(x,pivot)) ) lt ,
                  xs filter (x => x == pivot )           ,
                  qsort( xs filter (x => lt(pivot,x)) ) lt )
  }
```

/ 225

Scala (II)

Scala fuses (1) *object-oriented* and (2) *functional* programming in a statically typed programming language.

1. Scala uses a uniform and pure *object-oriented* model similar to that of Smalltalk: Every value is an object and every operation is a message send (that is, the invocation of a method).

In fact, even primitive types are not treated specially; they are defined as type aliases of Scala classes.

2. Scala is also a *functional* language in the sense that functions are first-class values.

/ 227

NB:

- ◆ Polymorphism.
- ◆ Type declarations can often be omitted because the compiler can infer it from the context.
- ◆ Higher-order functions.
- ◆ The binary operation $e \star e'$ is always interpreted as the method call $e.\star(e')$.
- ◆ The equality operation `==` between values is designed to be transparent with respect to the type representation.

/ 226

Mutable state

- ◆ Real-world objects with state are represented in Scala by objects that have variables as members.
- ◆ In Scala, all mutable state is ultimately built from variables.
- ◆ Every defined variable has to be initialised at the point of its definition.
- ◆ Variables may be `private`.

/ 228

Blocks

Scala is an *expression-oriented* language, every function returns some result.

Blocks in Scala are themselves expressions. Every block ends in a result expression which defines its value.

Scala uses the usual block-structured scoping rules.

/ 229

Parameter passing

Scala uses call-by-value by default, but it switches to call-by-name evaluation if the parameter type is preceded by `=>`.

Imperative control structures

A functional implementation of while loops:

```
def whileLoop( cond: => Boolean )( comm: => Unit )
{ if (cond)  comm ; While( cond )( comm ) }
```

/ 231

Functions

A function in Scala is a first-class value.

The anonymous function

```
( x1: T1, ... , xn: Tn ) => E
```

is equivalent to the block

```
{ def f ( x1: T1 , ... , xn: Tn ) = E ; f }
```

where `f` is a fresh name which is used nowhere else in the program.

/ 230

Classes and objects

- ◆ `classes` provide fields and methods. These are accessed using the dot notation. However, there may be `private` fields and methods are inaccessible outside the class.

Scala, being an object-oriented language, uses dynamic dispatch for method invocation. Dynamic method dispatch is analogous to higher-order function calls. In both cases, the identity of the code to be executed is known only at run-time. This similarity is not superficial. Indeed, Scala represents every function value as an object.

/ 232

- ◆ Every class in Scala has a superclass which it `extends`.

A class inherits all members from its superclass. It may also `override` (*i.e.* redefine) some inherited members.

If class `A` extends class `B`, then objects of type `A` may be used wherever objects of type `B` are expected. We say in this case that type `A` conforms to type `B`.

- ◆ Scala maintains the invariant that interpreting a value of a subclass as an instance of its superclass does not change the representation of the value.

Amongst other things, it guarantees that for each pair of types `S <: T` and each instance `s` of `S` the following equality holds:

```
x.asInstanceOf[T].asInstanceOf[S] = x
```

/ 233

- ◆ `abstract` classes may have *deferred* members which are declared but which do not have an implementation. Therefore, no objects of an abstract class may be created using `new`.

```
abstract class IntSet {  
  def incl( x:Int ): IntSet  
  def contains( x:Int ): Boolean  
}
```

Abstract classes may be used to provide interfaces.

/ 235

- ◆ Methods in Scala do not necessarily take a parameter list. These *parameterless* methods are accessed just as value fields.

The uniform access of fields and parameterless methods gives increased flexibility for the implementor of a class. Often, a field in one version of a class becomes a computed value in the next version. Uniform access ensures that clients do not have to be rewritten because of that change.

/ 234

- ◆ Scala has `object` definitions. An object definition defines a class with a single instance. It is not possible to create other objects with the same structure using `new`.

```
object EmptySet extends IntSet {  
  def incl( x: Int ): IntSet  
    = new NonEmptySet(x,EmptySet,EmptySet)  
  def contains( x: Int ): Boolean = false  
}
```

An object is created the first time one of its members is accessed. (This strategy is called *lazy evaluation*.)

/ 236

Case study (I)

- ◆ A `trait` is a special form of an abstract class that does not have any value parameters for its constructor and is meant to be combined with other classes.

```
trait IntSet {
  def incl( x:Int ): IntSet
  def contains( x:Int ): Boolean
}
```

Traits may be used to collect signatures of some functionality provided by different classes.

```
abstract class Expr {
  def isNumber: Boolean
  def isSum: Boolean
  def numValue: Int
  def leftOp: Expr
  def rightOp: Expr
}
class Number( n: Int ) extends Expr {
  def isNumber: Boolean = true
  def isSum: Boolean = false
  def numValue: Int = n
  def leftOp: Expr = error("Number.leftOp")
  def rightOp: Expr = error("Number.rightOp")
}
```

/ 237

/ 238

```
class Sum( e1: Expr; e2: Expr ) extends Expr {
  def isNumber: Boolean = false
  def isSum: Boolean = true
  def numValue: Int = error("Sum.numValue")
  def leftOp: Expr = e1
  def rightOp: Expr = e2
}
def eval( e: Expr ): Int = {
  if (e.isNumber) e.NumValue
  else if (e.isSum) eval(e.leftOp) + eval(e.rightOp)
  else error("bad expression")
}
```

? What is good and what is bad about this implementation?

Case study (II)

```
abstract class Expr {
  def eval: Int
}
class Number( n: Int ) extends Expr {
  def eval: Int = n
}
class Sum( e1: Expr; e2: Expr ) extends Expr {
  def eval: Int = e1.eval + e2.eval
}
```

/ 239

/ 240

This implementation is easily extensible with *new types of data*:

```
class Prod( e1: Expr; e2: Expr ) extends Expr {  
  def eval: Int = e1.eval * e2.eval  
}
```

But, is this still the case for extensions involving *new operations* on existing data?

/ 241

- ◆ Case classes and case objects implicitly come with implementations of methods `toString`, `equals`, and `hashCode`.
- ◆ Case classes implicitly come with nullary accessor methods which retrieve the constructor arguments.
- ◆ Case classes allow the constructions of *patterns* which refer to the case class constructor.

/ 243

Case study (III)

Case classes

```
abstract class Expr  
case class Number( n: Int ) extends Expr  
case class Sum( e1: Expr; e2: Expr ) extends Expr  
case class Prod( e1: Expr; e2: Expr ) extends Expr
```

- ◆ Case classes implicitly come with a constructor function, with the same name as the class.

Hence one can construct expression trees as:

```
Sum( Sum( Number(1) , Number(2) ) , Number(3) )
```

/ 242

Case study (III)

Pattern matching

The `match` method takes as argument a number of cases:

```
def eval( e: Expr ): Int  
= e match  
{  
  case Number(x) => x  
  case Sum(l,r) => eval(l) + eval(r)  
  case Prod(l,r) => eval(l) * eval(r)  
}
```

If none of the patterns matches, the pattern matching expression is aborted with a `MatchError` exception.

/ 244

Generic types and methods

- ◆ Classes in Scala can have type parameters.

```
abstract class Set[A] {  
  def incl( x: A ): Set[A]  
  def contains( x: A ): Boolean  
}
```

- ◆ Scala has a fairly powerful type inferencer which allows one to omit type parameters to polymorphic functions and constructors.

However, one can enforce *co-variant* subtyping by prefixing a formal type parameter with a `+`. There is also a prefix `-` which indicates *contra-variant* subtyping.

Scala uses a conservative approximation to verify soundness of variance annotations: a covariant type parameter of a class may only appear in co-variant position inside the class. Hence, the following class definition is **rejected**:

```
class Array[+A] {  
  def apply( index: Int ): A  
  ...  
  def update( index:Int , elem: A )  
  ...  
}
```

/ 245

/ 247

Generic types

Variance annotations

The combination of type parameters and subtyping poses some interesting questions.

? If `T` is a subtype of a type `S`, should `Array[T]` be a subtype of the type `Array[S]`?

! No, if one wants to avoid run-time checks!

In Scala, generic types like the following one:

```
class Array[A] {  
  def apply( index: Int ): A  
  ...  
  def update( index: Int, elem: A )  
  ...  
}
```

have by default *non-variant* subtyping.

/ 246

Functions are objects

Recall that Scala is an object-oriented language in that every value is an object. It follows that *functions are objects* in Scala.

Indeed, the function type

$$(A_1, \dots, A_k) \Rightarrow B$$

is equivalent to the following parameterised class type:

```
abstract class Functionk[-A1, ..., -Ak, +B]  
  { def apply( x1:A1, ..., xn:Ak ): B }
```

(Since function types are classes in Scala, they can be further refined in subclasses. An example are arrays, which are treated as special functions over the type of integers.)

/ 248

The function `x => x+1` would be expanded to an instance of `Function1` as follows:

```
new Function1[Int,Int] {
  def apply( x:Int ): Int = x+1
}
```

Conversely, when a value of a function type is applied to some arguments, the type's `apply` method is implicitly inserted; e.g. for `f` and object of type `Function1[A,B]`, the application `f(x)` is expanded to `f.apply(x)`.

NB: Function subtyping is contra-variant in its arguments whereas it is co-variant in its result. ? Why?

Generic types

View bounds

One problem with type parameter bounds is that they require forethought: if we had not declared `Num` as a subclass of `Ord`, we would not have been able to use `Num` elements in heaps. By the same token, `Int` is not a subclass of `Ord`, and so integers cannot be used as heap elements.

Generic types

Type parameter bounds

```
trait Ord[A] {
  def lt( that: A ): Boolean
}
case class Num( value: Int ) extends Ord[Num] {
  def lt( that: Num ) = this.value < that.value
}
trait Heap[ A <: Ord[A] ] {
  def insert( x: A ): Heap[A]
  def min: A
  def remove: Heap[A]
}
```

A more flexible design, which admits elements of these types, uses *view bounds*:

```
trait Heap[ A <% Ord[A] ] {
  def insert( x: A ): Heap[A]
  def min: A
  def remove: Heap[A]
}
```

A view bounded type parameter clause `[A <% T]` only specifies that the bounded type `A` must be *convertible* to the bound type `T`, using an implicit conversion.

Views allow one to augment a class with new members and supported traits.

Generic types

Lower bounds

Co-variant generic functional stacks:

```
abstract class Stack[+A] {
  def push[B >: A]( x: B ): Stack[B]
    = new NonEmptyStack(x,this)
  def top: A
  def pop: Stack[A]
}
class NonEmptyStack[+A]( elem: A, rest: Stack[A] )
extends Stack[A] {
  def top = elem
  def pop = rest
}
```

/ 253

Implicit parameters and conversions

◆ Implicit parameters

In Scala, there is an `implicit` keyword that can be used at the beginning of a parameter list.

```
def qsort[T]( xs: Array[T] )( implicit o: Ord[T] ): Array[T]
= if ( xs.length <= 1 ) xs
  else {
    val pivot = xs( xs.length/2 )
    Array.concat( qsort( xs filter ( x => o.lt(x,pivot)) ) ,
                  xs filter ( x => x == pivot ) ,
                  qsort( xs filter ( x => o.lt(pivot,x)) ) )
  }
```

/ 255

```
object EmptyStack extends Stack[Nothing] {
  def top = error("EmptyStack.top")
  def pop = error("EmptyStack.pop")
}
```

- ◆ Scala does not allow to parameterise objects with types.
- ◆ `Nothing` is a subtype of all other types.

/ 254

The principal idea behind implicit parameters is that arguments for them can be left out from a method call. If the arguments corresponding to implicit parameters are missing, they are inferred by the Scala compiler.

NB: View bounds are convenient syntactic sugar for implicit parameters.

◆ Implicit conversions

As last resort in case of type mismatch the Scala compiler will try to apply an implicit conversion.

```
implicit def int2ord( x: Int ): Ord[Int]
  = new Ord[Int] { def lt( y: Int ) = x < y }
```

Implicit conversions can also be applied in member selections.

/ 256

Mixin-class composition

Every class or object in Scala can inherit from several traits in addition to a normal class.

```
trait AbsIterator[T] {
  def hasNext: Boolean
  def next: T
}

trait RichIterator[T] extends AbsIterator[T] {
  def foreach( f: T=>unit ): unit =
    while (hasNext) f(next)
}
```

/ 257

```
object Test {
  def main( args: Array[String] ): unit = {
    class Iter extends StringIterator(args(0))
      with RichIterator[Char]
    val iter = new Iter
    iter foreach System.out.println
  }
}
```

The class `Iter` is constructed from a *mixin composition* of the parents `StringIterator` (called the *superclass*) and `RichIterator` (called a *mixin*) so as to combine their functionality.

/ 259

```
class StringIterator( s: String )
  extends AbsIterator[Char] {
  private var i = 0
  def hasNext = i < s.length
  def next = { val x = s.charAt i; i = i+1; x }
}
```

Traits can be used in all contexts where other abstract classes appear; however only traits can be used as *mixins*.

/ 258

The class `Iter` inherits members from both `StringIterator` and `RichIterator`.

NB: Mixture-class composition is a form of multiple inheritance!

/ 260

Language innovations

- ◆ Flexible syntax and type system.
- ◆ Pattern matching over class hierarchies unifies functional and object-oriented data access.
- ◆ Abstract types and mixin composition unify concepts from object and module systems.