


Inter-process communication (IPC)

- We have studied IPC via shared data in main memory.
- Processes in *separate address spaces* also need to communicate.
- Consider system architecture – both shared memory and cross-address-space IPC is needed
- Recall that the OS runs in every process address space:



Cross address-space IPC

1

Concurrent programming paradigms – overview

IPC via shared data – processes share an address space – we have covered:

1. shared data is a passive object accessed via concurrency-controlled operations:
conditional critical regions, monitors, pthreads, Java
2. active objects (shared data has a managing process/thread)
Ada select/accept and rendezvous
3. lock-free programming

We now consider: Cross-address-space IPC

Recall UNIX pipes – covered in Part 1A case study

Message passing – asynchronous – supported by all modern OS

Programming language examples:

Tuple spaces (TS)

Erlang – message passing between isolated processes in shared memory

Kilim – Java extension for shared memory message passing

Message passing – synchronous e.g. occam

Consider which of these might be used for distributed programming.

Cross address-space IPC

2

UNIX pipes outline - revision

A UNIX pipe is a synchronised, inter-process byte-stream

A process attempting to *read* bytes from an empty pipe is blocked.

There is also an implementation-specific notion of a “full” pipe

- a process is blocked on attempting to *write* to a full pipe.

(recall – a pipe is implemented as an in-memory buffer in the file buffer-cache.

The UNIX designers attempted to unify file, device and inter-process I/O).

To set up a pipe a process makes a *pipe* system call and is returned two file descriptors in its open file table. It then creates, using *fork* two children who inherit all the parent’s open files, including the pipe’s two descriptors.


Typically, one child process uses one descriptor to *write* bytes into the pipe and the other child process uses the other descriptor to *read* bytes from the pipe. Hence: pipes can only be used between processes with a common ancestor.

Later schemes used “named pipes” to avoid this restriction.

UNIX originated in the late 1960s, and IPC came to be seen as a major deficiency.

Later UNIX systems also offered inter-process message-passing, a more general scheme.

Asynchronous message passing - 1



Asynchronous message passing -2


Note no delay on *sendMess* in asynchronous message passing (OS buffers if no-one waiting)

Note cross-address-space IPC *implemented* by shared memory IPC in OS

Details of message header and body are system and language-specific e.g. typed messages.
At OS-level message transport probably sees a header plus unstructured bytes.

Need to be able to wait for a message from “anyone” as well as from specific sources
e.g. server with many clients

Client-server interaction easily set up
e.g. needed for system services in microkernel - structured OS.



Cross address-space IPC

5

Programming language example: Tuple spaces

Since Linda was designed (Gelernter, 1985) people have found the simplicity of tuple spaces (TS) appealing as a concurrent programming model. TS is logically shared by all processes.

Messages are programming language data-types in the form of tuples
e.g. (“tag”, 15.01, 17, “some string”)

Each field is either an expression or a formal parameter of the form *? var*,
where *var* is a local variable in the executing process

sending processes write tuples into TS, a non-blocking operation
out (“tag”, 15.01, 17, “some string”)

receiving processes read with a template that is pattern-matched against the tuples in the TS
reads can be non-destructive *rd* (“tag”, ? f, ? i, “some string”), which leaves the tuple in TS
or destructive *in* (“tag”, ? f, ? i, “some string”), which removes the tuple from TS

Even in a centralised implementation, scalability is a problem:

- protection is an issue, since a TS is shared by all processes.
- naming is by an unstructured string literal “tag” - how to ensure uniqueness?
- inefficient: the implementation needs to look at the contents of all fields, not just a header

Several projects have tried to extend tuple spaces for distributed programming
e.g. JavaSpaces within Jini, IBM Tspaces, various research projects.

Destructive reads are hard to implement over more than a single TS,
and high performance has never been demonstrated in a distributed implementation.

Cross address-space IPC

6

Programming language example: Erlang

Erlang is a functional, declarative language with the following properties:

1. single assignment – a value can be assigned to a variable only once, after which the variable is immutable
2. Erlang processes are lightweight (language-level, not OS) and share no common resources. New processes can be forked (*spawned*), and execute in parallel with the creator:

Pid = spawn (Module, FunctionName, ArgumentList)

returns immediately – doesn't wait for function to be evaluated

process terminates when function evaluation completes

Pid returned is known only to calling process (basis of security)

Pid is a first class value that can be put into data structures and passed in messages

3. asynchronous message passing is the only supported communication between processes.

Pid ! Message

! means send

Pid is the identifier of the destination process

Message can be any valid Erlang term

Erlang came from Ericsson and was developed for telecommunications applications.

It is becoming increasingly popular and more widely used.

Erlang – 2: receiving messages

The syntax for receiving messages is (recall guarded commands and Ada active objects):

receive

Message1 (when Guard1) ->

Actions1 ;

Message2 (when Guard2) ->

Actions2 ;

.....

end

Each process has a mailbox – messages are stored in it in arrival order.

Message1 and *Message2* above are patterns that are matched against messages in the process mailbox. A process executing *receive* is blocked until a message is matched.

When a matching *MessageN* is found and the corresponding *GuardN* succeeds, the message is removed from the mailbox, the corresponding *ActionsN* are evaluated and *receive* returns the value of the last expression evaluated in *ActionsN*.

Programmers are responsible for making sure that the system does not fill up with unmatched messages.

Messages can be received from a specific process if the sender includes its *Pid*

in the pattern to be matched: *Pid ! {self(), abc}*

receive {Pid, Msg}

Erlang – 3: example fragment

Client:

```
PidBufferManager ! { self ( ), put, <data> }  
PidBufferManager ! { self ( ), get, <pointer for returned data> }
```

Buffer Manager:

```
receive {PidClient, put, <data> } (buffer not full)  
insert item into buffer and return
```

```
{PidClient, get, <pointer for returned data> } (buffer not empty)  
remove item from buffer and return it to client
```

Erlang - 4: further information and examples

Part 1 of Concurrent Programming in Erlang is available for download from
<http://erlang.org/download/erlang-book-part1.pdf>

The first part develops the language and includes many small programs, including distributed programs, e.g. page 89 (page 100 in pdf) has the server and client code, with discussion, for an ATM machine.


The second part contains worked examples of applications, not available free.

A free version of Erlang can be obtained from
<http://www.ericsson.com/technology/opensource/erlang>

Erlang also works cross-address-space, and distributed.

Kilim – *shared address-space* message passing

Kilim extends Java via annotations and static checking. A **mailbox** paradigm is used.



- after writing a message into a mailbox the sending process/thread *loses all rights to that data*
- the receiver/reading-process gains rights. Based on **linear type theory**.
- in the current shared memory implementation, threads share an address space
 - messages are not physically copied but pointers are used i.e. mailboxes contain pointers
- good performance demonstrated for large numbers of threads cf. Erlang

Kilim further information

Sriram Srinivasan's PhD research, CL TR 769

After some 12 years' experience of developing web servers e.g. WebLogic, Ram wanted more efficient, but safe, concurrent programming with very large numbers of threads. The work is inspired by Ada and Erlang, but extending Java gives a better chance of acceptance and use.

Another motivation for Kilim was that in classical concurrency control, methods that execute under exclusion may make library calls, making it impossible for a compiler to carry out static checking of exclusive access to data.

For an overview, publications and download, see:

<http://www.malhar.net/sriram/kilim/>

Further work is to distribute Kilim, among other things ...

Synchronous and asynchronous systems

Historically, synchronous systems were favoured for theoretical modelling and proof.
e.g. occam was based on the CSP formalism, Hoare 1978

occam enforces static declaration of processes - more applicable to embedded systems than general purpose ones: “assembly language for the transputer”.
Current applications need dynamic creation of large numbers of threads.

In practice, asynchronous systems are used when large scale and distribution are needed.

See your theory courses for modelling concurrency and distribution.