

5 Numerical Methods (DJG)

- (a) Consider implementing the natural logarithm function $\ln(t)$ for floating-point numbers using the McLaurin series:

$$\begin{aligned}\ln(1+x) &= \sum_{n=1}^{\infty} (-1)^{n-1} \frac{x^n}{n} \\ &= x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots\end{aligned}$$

- (i) List all special behaviours the natural logarithm function should have in different parts of its range and when t takes the special values NaN and $\pm\infty$. [2 marks]
- (ii) The function must accept a broad range of numerical values but the series only converges when the absolute value of x is less than one, $|x| < 1$. Describe a range-reduction procedure that pre-processes the argument and post-processes the result so that the series always acts on small values of x . [6 marks]
- (iii) State the two precision requirements normally expected for mathematical libraries. Considering the worst-case value(s) of x after range reduction, approximately how many terms are needed to meet one of these requirements for a single-precision implementation? Do you expect the other requirement to be met? [6 marks]

- (b) The Trapezoidal Rule for numerical definite integration returns the area of the trapezium-shaped strips formed by each pair of adjacent points. The area under each such strip is:

$$\int_a^b f(x) dx \approx \frac{b-a}{2} [f(a) + f(b)]$$

- (i) A program computes the area between two points A and B using N strips of width h . What should be taken into account when choosing h ? Suggest a good value for h . [3 marks]
- (ii) Assuming the best choice for h , what characteristics of $f()$ will affect the accuracy achieved? [3 marks]