

# Database Theory: Exercise Sheet 1

Anuj Dawar  
anuj.dawar@cl.cam.ac.uk

May 11, 2003

1. (The exercise on Slide 34). Suppose  $\phi$  is a conjunctive formula,  $x$  is a free variable occurring in  $\phi$ ,  $\mathcal{I}$  a database instance and  $\nu$  a valuation of the variables such that  $\nu(x) \notin \text{adom}(\mathcal{I})$ . Prove, by induction on the structure of  $\phi$ , that  $\mathcal{I} \not\models_{\nu} \phi$ .
2. (The exercise on Slide 64). Let  $P$  be a Datalog program, and  $T_P$  be defined as on slide 63. If  $\mathcal{I}$  and  $\mathcal{J}$  are two database instances such that  $\mathcal{I} \subseteq \mathcal{J}$  and  $R$  is a relation in  $\text{idb}(P)$ , show that  $T_P(\mathcal{I})(R) \subseteq T_P(\mathcal{J})(R)$ .
3. Prove the assertion on slide 72. That is, if  $\mathcal{I}$  and  $\mathcal{J}$  are such that  $\mathcal{I} \subseteq \mathcal{J}$  and they agree on all *extensional* relations and  $P$  is a **semipositive** Datalog program, then for each  $R$  in  $\text{idb}(P)$   $T_P(\mathcal{I})(R) \subseteq T_P(\mathcal{J})(R)$ . Use this to show that any query defined by a **semipositive** Datalog program is monotone in the restricted sense of slide 73.
4. Consider the following questions one might ask of the *Cinema* database:
  - Is there a film directed by Almodovar playing in Cambridge?
  - Which directors have appeared in every film they've directed?
  - List all films in which Allen acted or directed.
  - (a) For each of these, write a relational calculus query that defines it.
  - (b) Which of these queries is definable in the conjunctive calculus? Which of them is definable in Datalog? For each such, write a Datalog program to define it.
  - (c) For any query in the list that is not definable in Datalog, prove that it is not (by constructing an appropriate example).
  - (d) For queries above not definable in Datalog, state whether they are definable in **semipositive** Datalog. Either give a program or a reason why it's inexpressible.
5. Given the *Railway* database of slide 56, write Datalog programs to compute the following queries:
  - (a) List all stations that are reachable from both Oxford and Cambridge.
  - (b) List all stations that are reachable from either Oxford or Cambridge.

6. Suppose we have a database with two relations. One is the *Railway* relation of slide 56. The other is a similar relation *Coach*[*Service, From, To*]. Write programs in stratified Datalog to express the following queries:
  - (a) List the pairs of stations  $x, y$  such that one can go from  $x$  to  $y$  by train but not by coach.
  - (b) List the pairs of stations  $x, y$  such that one can go from  $x$  to  $y$  by coach in such a way that for no leg of the journey is there a possible train connection.
7. For the queries in 5 above, write expressions of the fixed-point calculus.
8. For all the queries in 5 and 6 above, give an upper bound on the complexity of evaluating the query.
9. Take it as given (as stated on slide 97) that we can construct, for each  $m$  two graphs  $G_m$  and  $H_m$ , one consisting of a single cycle and one consisting of two disjoint cycles such that **Duplicator** has a winning strategy in the  $m$ -move Ehrenfeucht game played on these two graphs. Show why this implies that the query at the top of slide 86 (*Is there a way to travel around Britain so that I visit every railway station exactly once*) is not definable in the relational calculus.