General Processor Information

Copyright 1994-1999 Tom Burd
Last Modified: October 26, 1999

(DISCLAIMER: SPEC performance numbers are the highest rated for a given processor version. Actual performance depends on the computer configuration, and may be less, even significantly less than, the numbers given here. Also note that non-italicized numbers may be company estimates of perforamnce when actual numbers are not available)

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Intel x86	8086	[vi]	78	v/16	5	-	-	-	-	1/1	1/1/na	-	-	5.0	3.0					0.029
					8	-	-	-	-											
					10	-	-	-	-											
	8088	[vi]	79	v/16	5	-	-	-	-	1/1	1/1/na	-	-	5.0	3.0					0.029
					8	-	-	-	-											
	80186	[vi]	82	v/16		-	-	-	-	1/1	1/1/na	-	-	5.0	1.5					
	80286	[vi]	82	v/16	6	-	-	-	-	1/1	1/1/na	-	-	5.0	1.5					0.134
					10	-	-	-	-											
					12	-	-	-	-											
	i386DX	[vi]	85	v/32	16			-	-	1/1		-	-	5.0	1.5					0.275
			87		20			-	-											
			88		25			-	-											
			89		33	9.4		-	-						1.0	2				
	i386SX	[vi,41]	88	v/32	16			-	-	1/1	4/na/na	-	-	5.0	1.5					0.275
		[vi]	89		20			-	-						1.0	2				
			89		25			-	-											
			92		33	6.2	3.3	-	-								~2		43	
	i386SL	[vi]	90	v/32	20			-	-	1/1	4/na/na	-	-	5.0	1.0	2				0.855
			91		25			-	-											

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Intel x86	i486DX	[vi]	89	v/32	25	16.8	7.4	-	-	2/1	5/na/5?	8 u.	4	5.0	1.0	2				1.2
		[vi,45]	90		33	22.4		-	-											
		[vi]	91		50	33.4	14.5	-	-						0.8	3	5.0	3.9	81	
	i486SX	[vi]	91	v/32	16			-	-	2/1	5/na/5?			5.0	1.0	2				1.185
		[vi]			20			-	-											
		[vi]			25	12		-	-											
		[vi]	92		33	15.9		-	-						0.8	3				0.9
	i486SL	[vi]	92	v/32	20			-	-	2/1	5/na/5?				0.8	3				1.4
					25			-	-											
					33			-	-											
	i486DX2	[vi]	92	v/32	50	*29.9*	*14.2*	-	-	2/1	5/na/5?	8 u.	4	5.0	0.8	3			81	1.2
		[vi,20]			66	*39.6*	*18.8*	-	-								7.0	4.9		
	i486DX4	[vi]	94	v/32	75	*41.3*	*20.1*	-	-	2/1	5/na/5?	16 u.	4?	3.3	0.6	4			345	1.6
		[vi,42]			100	*55*	*27*	-	-									4		
	P5	[vi]	93	v/32	60	*70.4*	*55.1*	-	-	3/2	5/na/8	8/8	2/2	5.0	0.8	3			296	3.1
		[2,10]	93		66	*78*	*63.6*	-	-								16.0			

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Intel x86	P54VRT (Mobile)	[vi,sp]	94	v/32	75	*89.1*	*68.5*	*2.4*	*2.1*	3/2	5/na/8	8/8	2/2	2.9	0.6	4	5.2	2.4		3.1
		[vi,sp]	94		90	*110*	*84.4*	*2.9*	*2.5*								6.5	3.0		
		[vi]	96		120	157	108	*3.8*	*3.0*											
		[mr,vi]	96		133	174	121	*4.2*	*3.3*									3.3		
		[vi]	96		150			*4.6*	*3.3*					3.1				3.8		
	P54C	[2,11,vi]	94	v/32	100	*122*	*93.2*	*3.3*	*2.8*	3/2	5/na/8	8/8	2/2	3.3	0.6	4	5.0		148	3.1
	P54CQS	[47,vi]	95	v/32	120	157	108	*3.8*	*3.0*	3/2	5/na/8	8/8	2/2	3.3	0.35	4	10.0		90	3.1
	P54CS	[53,vi]	95	v/32	133	174	121	*4.2*	*3.3*	3/2	5/na/8	8/8	2/2	3.3	0.35	4			90	3.1
		[31,vi]	96		150	181	125	*4.3*	*3.3*											
		[vi]			166	198	138	*4.8*	*3.7*											
		[vi]			200			*5.5*	*4.2*					3.45						
	P55C (MMX)	[vi]	97	v/32	166			*5.6*	*4.3*	5/2	6/na/8	16/16	4/4	2.8	0.35	4			141	4.5
		[vi]			200			*6.4*	*4.7*								15.7			
		[vi]			233			*7.1*	*5.2*								17			
		[vi]			266															
	P55VRT (Mobile MMX)	[vi]	97	v/32	166			*5.6*	*4.3*	5/2	6/na/8	16/16	4/4	2.45	0.35	4	7.8		141	4.5
		[vi]	97		166									1.8	0.25	4 ?		2.9		
		[vi]			200			*6.4*	*4.7*									3.4		
		[vi]			233			*7.1*	*5.2*									3.9		
		[vi]	98		266									2.0				5.3		
	P6 (Pentium Pro)	[vi]	95	v/32	150	245	220	*6.1*	*5.4*	7/?	14/14/16 (D)	8/8(L)	4/2	3.1	0.6	4	29.2	23.2	306(L)	5.5
					180			*7.3*	*6.1*					3.3	0.35	4			195(L)	
					200	320	283	*8.2*	*6.8*					3.3	0.35	4	35	28.1		
		[vi]	96		166	293	261	*7.3*	*6.2*	7/?	14/14/16 (D)	8/8(M)	4/2	3.3	0.35	4	29.4	23.4	195(M)	
					200			*8.7*	*6.7*					3.3	0.35	4				
		[vi]	97		200			*8.7*	*6.8*		14/14/16 (D)	8/8(N)	4/2	3.3	0.35	4			195(N)	

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Intel x86	Pentium II (Klamath)	[vi]	97	v/32	233			*9.5*	*6.4*	7/?		16/16	4/4	2.8	0.35	4			203	7.5
		[vi]			266			*10.8*	*6.9*											
		[vi,is97,sp]			300			*11.9*	*8.6*											
	Pentium II (Deschutes)	[vi]	98		333			*13.0*	*9.6*						0.25				131	
		[vi,by]			350			*13.9*	*11.2*					2.2						
		[vi]			400			*15.8*	*12.4*											
		[vi,is98]			450			*17.2*	*12.9*											
	Mobile Pentium II (Deschutes)	[vi]	98		233			*9.5*	*6.4*						0.25				131	
		[vi]			266			*10.8*	*6.9*											
		[th]			300			*11.9*	*8.6*											
	Celeron (Deschutes)	[vi]	98		266			10.8	6.9						0.25		15.6		131	
		[vi]			300			11.9	8.6								17.5			
	Pent II Xeon (Deschutes)	[vi]	98		400			*16.5*	*13.7*					2.0	0.25		23.3		131	
		[vi]			450			*18.9*	*14.7*											
	Pent III (Katmai)	[vi]	99	v/32	450			*18.7*	*13.7*					2.0	0.25					9.5
					500			*20.6*	*14.7*											
					550			*22.2*	*15.0*											
					600			*24.0*	*15.9*											
	Pent III Xeon (Katmai)	[vi]	99	v/32	500			*20.6*	*14.7*					2.0	0.25					
					550			*22.2*	*15.0*											

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Intel x86	Celeron (Mendocino)	[vi]	98	v/32	300			*12.0*	*9.7*			16/16 128	?/? ?	2.0	0.25		17.5			19.0
					333			*13.1*	*10.4*								19.4			
			99		366			*14.1*	*11.2*								21.4			
					400			*15.1*	*11.8*								23.4			
					433			*16.1*	*12.1*											
					466			*17.0*	*12.7*											
					500			*17.9*	*12.9*											
	Mobile Celeron (Mendocino)	[vi]	99	v/32	266							16/16 128	?/? ?	1.6	0.25			7.0		18.9
					300			12.0	9.7									7.7		
					333			13.1	10.2									8.6		
					400													9.2		
	Mobile Pentium II (Dixon)	[vi]	99	v/32	266							16/16 256	?/? ?	1.6	0.25			7.0		27.4
					300													7.7		
					333													8.6		
					366													9.5		
					400									1.55				8.7		
		[vi]	99		400									1.5	0.18			7.5		

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Intel x86	Pentium III (Coppermine)	[vi]	99	v/32	500							16/16 256	?/? 8	1.6	0.18	6			106	28
					533															
					550															
					600															
					650															
					667															
					700			*33.0*	*29.0*											
					733			*35.6*	*30.4*											
	PentIII Xeon (Coppermine?)	[vi]	99	v/32	600							16/16 256	?/? 8	1.6	0.18	6			106	28
					667			*33.0*	*29.0*											
					733			*35.6*	*30.4*											
	Mobile Pentium III (Coppermine)	[vi]	99	v/32	400							16/16 256	?/? 8		0.18	6			106	28
					450									1.6						
					500															
	Celeron (Coppermine)	[th]	1Q00	v/32	450							16/16 128	?/? 8		0.18	6				
					500									1.6						
			2Q00		550															
	PentIII Xeon (Tanner)	[th],[re]	99		450										0.25					
					500															
	PentIII Xeon (Cascades)	[th]	99		533+										0.18					
	Itanium (Merced)	[vi]	00	v/64																

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Cyrix/ IBM x86	486SLC	[vi,cm]	92?	v/32	20					1/1									72	0.6
		[vi]			33															
	486DX4	[vi,cm]	93?	v/32	100					2/1		8 u.	4	3.0					196	1.1
	5x86 (M1sc)	[vi]	95	v/32	100					2/1	6/6/?	16 u.	4	3.45	0.65	3	3.5	3	144	2.0
		[vi]	95	v/32	120					2/1	6/6/?	16 u.	4	3.3	0.65	3			144	2.0
	5gx86 (MediaGX)	[is96]	96	v/32	120					2/1	6/6/?(O)	16 u.	4	3.3	0.6	3			160	2.4
		[vi]	97		133															
		[vi]	97		150	(PR150)									0.5	3				
		[vi]	98		233															
	6x86 (M1)	[46]	95	v/32	100					3/2	7/7/?	16 u.	4	3.3	0.65	3	10		394	3.0
		[pn,vi]			120											5			210	
	6x86 (M1R)	[vi]	96	v/32	100	(PR120)				3/2	7/7/?	16 u.	4	3.3/ 2.8	0.5	5			169	3.0
		[vi]			110	(PR133)														
		[vi]			120	(PR150)														
		[pn,vi]			133	(PR166)														
		[vi]			150	(PR200)									0.44				169	
	6x86MX (MII)	[vi]	97	v/32	150	(PR166)				3/2	7/7/?	64 u.	4	2.9	0.35	5			197	6.0
		[vi,55]			166	(PR200)		~5.1	~2.2											
		[vi,55]			188	(PR233)			~2.7											
		[vi]	97		208	(PR266)														
		[vi]	98		233	(PR300)									0.3	5				
		[vi]	98		250	(PR333)														
	MXi (Cayenne)	[vi]	98-99	v/32		(PR300)						64 u.			0.25	5			~90	
						(PR400)														
	M3 (Jalapeno)	[vi]	00	v/32	600-800						11/?/?	? u. 256	? ?		.18				~120	

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Nexgen (AMD)	Nx586	[42,43]	95	v/32	93					5/1(D)	7/9/na(D)	16/16		4.0	0.5	5	16	9	199	3.5
		[vi]	95	v/32	133					5/1(D)	7/9/?(D)	16/16		3.6	0.44	5			118	

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
AMD	386	[cm]	90																	
	Am486	[pn]	95	v/32	120					2/1					0.5	3		~3		
	Am5x86	[vi]	95	v/32	133					2/1		16 u.			0.35	3			43	
	Am5k86	[39,vi]	95	v/32	75	(PR75)				6/?	5/5/5?	16/8	4/4	3.5	0.35	3			161	4.3
					90	(PR90)														
			96		100	(PR100)														
	K5	[39,vi]	96	v/32	90	(PR120)				6/?	5/5/5?	16/8	4/4	3.5	0.35	3			161	4.3
					105	(PR133)											14			
			97		120	(PR166)														
	K6	[vi, is97, 55]	97	v/32	166					7/?	6/7/7(D)	32/32	2/2	2.9	0.35	5	17.2	10.3	162	8.8
					200			~6.2	~3.5								20	12		
					233			~6.8	~3.8					3.2			28.3	17		
		[by]			266															
		[vi]			266										0.25	5			68	8.8
		[vi]	98		300															
	K6-2 (K6-3D)	[vi]	98	v/32	266					7/?	6/7/7(D)	32/32	2/2		0.25	5			81	9.3
					300															
					333															
					350															
					400															
			99		450															
					475															
					500															

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
AMD	Mobile K6-2-P	[vi]	99	v/32	350					7/?	6/7/7(D)	32/32	2/2	2.2	0.25	5			81	9.3
					366															
					380															
					400													12		
					433															
					450															
					475															
	K6-III (K6+-3D)	[vi]	98	v/32	400					7/?	6/7/7(D)	32/32 256			0.25	5			135	21.3
			99		450															
	Mobile K6-III-P	[vi]	99	v/32	380					7/?	6/7/7(D)	32/32 256		2.2	0.25	5		12	135	21.3
					400									2.0						
					433															
					450															
	Athlon (K7)	[vi]	99	v/32	500					9/?		64/64			0.25	6	42	38	184	22.0
					550			23.6	20.6								46	41		
					600			27.5	22.2								50	45		
					650			29.7	23.2								54	48		
					700			31.7	24.0								50	45		
			00												0.18	?				
	K8	[vi]	00/1	v/64																

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
IDT	WinChip (C6)	[vi,55]	97	v/32	200			~4.1	~2	3/1(D)	5/5/?	32/32	2/2	3.3	0.35	4			88	5.4
		[vi]			225									3.5						
		[vi]			240															
	WinChip2 (C6+)	[vi]	98	v/32	200					6/2-	6/6/?	32/32	2/4	3.3	0.25	5			58	5.8
		[vi]			225															
		[vi]			233															
		[vi]			240									3.5						
		[vi]			266															
		[vi]	99?		300															
	WinChip3	[vi]	99	v/32	266							64/64							75	
	WinChip4	[vi]	2H99	v/32	4-500					4/2	11/?/?	64/64	2/4	2.5	0.25	6	16		95	
		[vi]	1H00		5-700									1.8	0.18				60	

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Mot 68k	68020	[45]	85	v/32	25	NA	NA			1/1	?/na/na	NA/.25	NA/1	5.0	1.5	2				
	68030	[41,45]		v/32	50		NA			1/1	3/na/na	.25/.25	1/1	5.0	1.2	2			55	0.27
	68040	[10,45]	89	v/32	25	21	15			2/1	6/na/6	4/4	4/4	5.0	0.8	3	6.0		164	1.2
		[vi]	94?	v/32	66															
	68060	[15,21]	93	v/32	50	~60(B)	~45(B)			3/2	8/na/8	8/8	4/4	3.3	0.5	3	3.9		198	2.4

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Power PC	601	[15,25]	93	32	50	40	60			4/3	4/5/6	32 u.	8	3.6	0.6	4	9.1	6.5	121	2.8
	601v	[9,vi]	94	32	100	105	125			4/3	4/5/6	32 u.	8	3.3	0.5	5	5.6	4.0	74	2.8
		[vi]	95		120															
	602	[43]	95	32	66	40				4/2	4?/5?/6?	4/4	2/2	3.3	0.5	4		1.2	50	1.0
	603	[2,6,25]	94	32	80	75	85			4/2	4/5/6	8/8	2/2	3.3	0.5	4	3.0	2.2	85	1.6
	603e	[44, vi]	95	32	100	120	105			4/2	4/5/6	16/16	4/4	3.3	0.5	4	3.5		98	2.6
			96		200			5.3	4.0					2.5	0.35	5			80	
					240			6.3	4.6								5.5			
		[vi]	97		250										0.25	5			42	
		[vi]			275															
		[vi]			300			7.4	6.1									~3.5		
	603q	[vi]	96	32	160	120	84			2/1	5/5/5?	16/8	4/2	3.3	0.5	3		1.2	69	
	604	[7,8,vi]	94	32	100	128(H)	120(H)	*3.6*	*3.2*	6/4-	4/5/6	16/16	4/4	3.3	0.5	4		14	197	3.6
		[53,vi,sp]	95		133	176(H)	157(H)	*4.7*	*3.8*									17.5		
		[vi]	96		180			*6.2*	*5.3*											
	604e	[mw,vi]	96	32	166			*6.7*	*6.3*	6/4-	4/5/6	32/32	4/4	2.5	0.5	5	15	10	148	5.1
		[sp]			200			*9.3*	*8.9*								19.5	12		
		[vi]			225			10.2	*7.6*											
		[vi]	97		200			*9.3*	*8.9*						0.35		16	14.5	96	
		[vi]			233			10.3	7.3									~15		
		[vi]			250			11.1	7.8					1.9	0.25	5		6	47	
		[vi]			300			12.9	8.5								12	6.8		
		[vi]			333			13.9	8.6									7.5		
		[vi]			350			14.6	9.0									8		
		[vi]			375			15.9	10.1											

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Power PC	620	[pn,43]	95	64	133	225	300	6.0	6.0	6/4-	4/5/6	32/32	8/8	3.3	0.5	4	30.0		311	7.0
		[vi]	96		200			9.0	~9			64/64		2.5	0.35	5	30			
	x704	[vi,is97]	97	32	533			12	10	?/3	6/6?/6?	2/2 32	?/? ?	3.6	0.5	5	85		150	2.7
	740 (G3)	[vi-mot]	97	32	200					6/3	4/5?/6?	32/32	8/8	2.5	0.29	5			67	6.35
		[vi-mot]			233															
		[mw]			266			11.5	6.9									5.7		
		[vi-mot]	98											1.9	0.25					
		[vi-mot]			300			12.2	7.1								4.2	3.4		
	750 (G3) (was 613)	[vi]	97	32	200					6/3	4/5?/6?	32/32	8/8	2.5	0.29 (mot) 0.25 (ibm)	5			67	6.35
		[vi]			233			11.0	8.1								7.0	5.6		
		[vi]			250			11.8	8.7											
		[mw,is97]			266			12.4	8.4								7.9	6.5		
		[vi]	98		275			12.9	8.6								8.2	6.7		
		[vi]			300			14.0	9.4					2.6			9.0	7.3		
		[vi-mot]												1.9	0.25	5	4.2	3.4	67	
		[vi-mot]			333			16.0	10.9											
		[vi-ibm]													0.22	6	4.7	4.1	40	
		[vi-ibm]			350			16.6	12.0								5.0	3.8		
		[vi-mot]			366			16.1	9.9						0.25	5	6.5	5.0	67	
		[vi-ibm]													0.22	6	5.2	4.4	40	
					375			17.8	11.5											
					400			19.2	13.1					2.1			5.7	4.7		
			99		450			21.4	13.8									5.2		
					466			21.8	12.6									5.5		

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Power PC	RS64	[vi-ibm]	98	64	125							64/64								
	RS64-II	[vi-ibm]	98	64	262					5/4		64/64								
	7400 (G4)	[vi-mot]	99	64	350					7/3-		32/32		1.8	0.15	6			83	6.5
					400												8.0	5.0		
					450			21.4	20.4					2.15						
			3Q99		500															
Power	P2SC	[vi]	97	32	120			*5.6*	*16.6*	10/6-		32/128		2.5	0.29	5			335	15
		[vi]	97		135			*6.2*	*17.6*								30			
		[vi]	98		160			*8.6*	*26.6*											
	Power3	[vi]	98	64	200			13.2	30.1		5?/5?/?	32/64			0.25	5			270	
		[vi]	99		300										0.2				160	
		[vi]	99		500										0.18					

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Sparc	CY7C601	[19,20]	90?	32	40	21.8	22.8			1/1	5/na/na	na/na	na/na	5	0.8	2	3			
	Weitek 2x	[20]	92?	32	80	32.2	31.1			1/1		16/8			0.8					1.8
	Micro	[20,41]	91?	32	50	26.4	21.0			1/1		4/2		5	0.8	2	4		225	
	Micro 2	[20,37]	94	32	85	*65.3*	*54.6*			1/1	5/na/5?	16/8			0.5	3			233	2.3
		[vi]	95	32	110	*79*	*65*	*1.6*	*2.0*						0.4	3	9			
	Micro 3		97	64																
	Hyper (Ross)	[20]	93?	32	72	80	105			4/2-	6/6/6	8/na	?/na		0.8					
		[37]	94	32	100	*112*	*127*			4/2-	6/6/6	8/na	?/na		0.5	3			327(C)	1.7(C)
		[49]	95	32	125	159	183			4/2-	6/6/6	8/na	?/na		0.4					
		[pn,vi]	95	32	150	180	245	*4.1*	*4.9*	4/2-	6/6/6	8/na	?/na		0.4					
		[pn,vi]	96	32	200	235		*5.3*	*5.1*	4/2-	6/6/6	16/16			0.35					
	Super	[10,20,vi]	92	32	60	89	103	~1.5	~1.7	5/3	4/4/5	20/16	5/4	5.3	0.6	3	14.2		256	3.1
	Super 2	[29,37,vi]	95	32	75			*3.1*	*3.1*	5/3	4/4/5	20/16	5/4	5?	0.6	3			299	3.1
					90	135	147	~3.5	~3.5								16			
	Thunder 1	[21]	93	32	50	120	240			8/4				5	0.6					~6

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Sparc	Ultra I	[35,43,vi]	95	64	167	269	386	*6.6*	*9.4*	9/4	9/9/9	16/16	2/1	3.3	0.47	4	30		315	5.2
	Ultra I+	[vi]	95	64	200	322	462	*7.8*	*11.4*	9/4	9/9/9	16/16	2/1	3.3	0.42	4	30		265	5.2
	Ultra II	[vi]	96	64	250	~350	~550	*10.4*	*15*	9/4	9/9/9	16/16	2/1	2.6	0.35	5	~25		149	5.4
		[vi]	97		300			*12.1*	*18.8*											
		[vi]	98		360			16.1	23.5											
		[vi]			400									1.9	0.25			21	126	
		[vi]			450			19.6	27.1											
	Ultra IIi	[vi]	98	64	270			9.2	10.1	9/4	9/9/9	16/16	2/1	2.6	0.35	5			156	5.4
		[vi]			300			12.1	12.9											
		[is97,vi]			333			14.2	16.9								<30			
		[vi]			360			15.2	19.9											
		[vi]			440									1.9	0.25					
		[vi]			480															
	Ultra III	[vi]	99	64	600			35+	60+						0.25					
		[vi]	99/00	64											0.18					
	SPARC64	[vi,43] (HAL)	95	64	118			*5.1*	*9.5*	9/4	4/6/7	64/64 (F)	4/4	3.3	0.4	4				2.7/ 21.9(G)
	SPARC64II		96		141			*7.5*	*12.2*											
			96		161	256	330	*8.5*	*15.3*								?/60(G)			
	Turbo (Toshiba)	[vi]	96	64	170	143	119	3.5	3.0			16/16		3.3	0.35	4	9	7	132	3.0
	Viper (Ross)	[vi]	98	64																

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Alpha	21064	[vi]	92	64	100	*75*	*95*	*1.9*	*2.8*	4/2-	7/7/10	8/8	1/1	3.3	0.75				234	1.68
		[vi]			133	*75*	*112*													
		[vi]			150	*84*	*128*	*2.2*	*3.7*											
		[vi]			166	*116*	*135*	*3.0*	*3.6*											
		[vi]			175	*114*	*162*													
		[1,4,23]			200	*138*	*200*										30			
	21064a	[vi]	94	64	225	*163*	*231*	*3.7*	*5.7*	4/2-	7/7/10	16/16	1/1	3.3	0.5	4			164	2.8
		[vi]			233	*165*	*223*	*4.3*												
		[vi]			266	*199*	*263*	*5.2*	*6.3*											
		[18,23]			275	*203*	*293*	*5.2*	*6.3*								33			
		[vi]	95		300	220	300	*5.2*	*6.5*											
	21066a	[vi]	93	64	166	77	110			4?/2-	7/7/10	8/8	1/1	3.3	0.5	4			161	1.75
		[vi]	94		225	*135*	*205*													
		[34,37]			233												23			
		[vi]			275	*170*	*240*													
	21164	[vi]	94	64	266	*329*	*429*	*7.9*	*11.8*	4/4-	7/7/9	8/8 96	1/1 ?	3.3	0.5	4			299	9.3
		[22,21]			300	*341*	*513*	*8.5*	*12.7*								50			
		[vi]	95		333	*412*	*542*	*9.8*	*13.4*											
	21164PC	[vi,is97]	97	64	400					4/4-	7/7/9	16/8	1/1	2.5	0.35	4	27		138	3.5
		[vi]	97		466			*14.6*	*17.4*								31.5			
		[vi]	97		533			16.1	18.8								36			
		[vi]	97		600			17.9	19.9								40.5			
	21164a	[vi]	96	64	400	~500	~750	*12.3*	*17.2*	4/4-	7/7/9	8/8 96	1/1 ?	2.0	0.35	4	30.5		209	9.3
		[vi]	96		433			*13.9*	*18.1*								33			
		[vi]	96		500			*15.0*	*20.4*								38			

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d/L2)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Alpha	21264	[vi]	98	64	575			*30.3*	*47.7*	6/4	7/7/10	64/64	2/2	2	0.35	6	~60		302	15.2
		[vi,is97]	98		667			44	66								72			
		[vi]	98		700										0.25					
	21264PC	[by]	98	64						6/4	7/7/10				0.25					
	21264a	[cg,by]	98	64	800					6/4	7/7/10				0.35					
		[vi]	99												0.25					
		[vi]	00												0.18					
	21364	[cg,by]	00		1000			~70	~120	6?/4	6/6/?	64/64 1500	2/2 6	1.5	0.18	6	100		350	100
	21464	[cg]	03												0.18					~250

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
MIPS	R2000	[mc]	86	32																0.11
	R3000	[12,20]	88	32	40	27.9	35.8			1/1	5/na/na	na/na	na/na	5.0	1.2		4.0			
	R6000(E)	[20,32]	91	32	66.7	40.6	45.1			1/1	5?/na/na	na/na	na/na						(E)	
	R4000	[20,32]	92	64	100	*59*	61			2/1	8/na/10	8/8	1/1		1.0				213	1.1
	R4200	[2,5]	93?	64	80	55	30			1/1	5/na/5	16/8	1/1	3.3	0.64	3	1.8	1.5	78	1.4
	R4300i	[52]	95	64	100	60	45			1/1	5/na/5	16/8	1?/1?	3.3	0.35	3		1.8	45	1.7
		[vi]	96	64	133													2.2		
	R4400	[10,17,sp]	92	64	150	109	97			2/1?	8/na/10	16/16	1/1	3.3	0.6	3	15		186	2.3
		[37,38]	94	64	200	*146*	143	*4.3*	?						0.5	2			148	2.2
		[53,sp]	95	64	250	180	178	5.1							0.35				108	~2.2
	R4600	[13,37]	94	64	150	114	83			2/1	5/na/5	16/16	2/2	3.3	0.64	3	4.6	3.0	77	1.85
	R4700	[37,vi]	95	64	175	132	105			2/1	5/na/5	16/16		3.3	0.6	3	3.5		73	1.85
	R5000	[sp]	96	64	180			*4.8*	*5.4*	3/2-	5/na/8	32/32	2/2	3.3	0.35	3			84	3.6
		[vi]	96		200			5.5	5.5								10			
		[vi]	96		250															
	R5000A	[vi]	97	64																
	RM5271	[vi]	99	64	300										0.25					
	RM7000	[vi]	97	64	300			~13	~15	?/2		16/16	4/4		0.25	4	13		80	
	R8000	[20,37]	94	64	75	*112*	*311*			6/4-	5/5/?	16/16	1/1	3.3	0.7	3			596(C)	3.43(C)
		[vi]	95	64	90	132	396								0.5		~30			

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
MIPS	R10000	[vi]	96	64	180			*10.3*	*15.6*	5/4	5/6/7	32/32	2/2	3.3	0.35	4			298	6.8
		[vi]	96		195	300	600	*11.4*	*19.1*								~30			
		[vi]	98		250			*14.7*	*24.5*											
		[vi]	98?		275			>12	>24											
	R12000	[vi]	98	64	270			15.8	25.2											
					300			18.4	34.4											
	H1	[vi]	99																	
	H2	[vi]	00																	

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
ARM	610	[3,15,27]	93	32	25	16	NA			1/1	3/na/na	4 u.	64	5.0	1.0	2	0.5		71	0.36
	710	[27]	94	32	33		NA			1/1	3/na/na	8 u.	4	5.0	0.8	2	0.5		46	0.54
	810	[vi]	96	32	75		NA			1/1	5/na/na	8 u.	4?	3.3	0.5	3	0.5?			
	SA-110	[vi,is96]	96	32	160		NA			1/1	5/na/na	16/16	32/32	1.65	0.35	3		0.5	50	2.1
					200		NA							2.0				0.9		
			96	32	233		NA											1.0		
	SA-1100	[vi]	97	32	133		NA			1/1	5/na/na	16/8	32/32	1.5	0.35	3	0.3	0.2		2.5
					200		NA										0.45	0.25		
	940T	[vi]	98	32	150		NA			1/1	5/na/na	4/4	64/64	3	0.35		0.68		15	
	1020T	[vi]	99?	32	300								32/32		0.25					

Processor		Source	Date (ship)	Bits (i/d)	Clock (MHz)	SPEC-92		SPEC-95		Units / Issue	Pipe Stages int/ldst/fp	Cache (i/d)		Vdd (V)	Tech (um)	Met	Power (W)		Size (mm^2)	Xsistor (10^6)
						int	fp	int	fp			kB	Assoc				peak	typ		
Hobbit	92010	[3,15]	92	32	20	8	NA			1/1	3/na/na			3.3	0.9		0.25			
	92020S	[40]	94	32			NA													
PA-RISC	7000	[32,54]	89	32	50			*1.6*	*2.0*	1/1	5/na/na	na/na	na/na							
			91		66	51	82								1.0				196	0.58
	HARP-1	[41]		32	120	70	120													
	7100	[3,10,sp]	92	32	100	*124*	*159*	*3.2*	*4.0*	2/2-	5/na/6	na/na	na/na	5.0	0.8	3	23.0		202	0.85
	7150	[24,sp]	94?	32	125	*149*	*201*	*5.2*	*4.6*	2/2-	5/na/6?	na/na	na/na	5.0	0.8	3	30		196	0.85
	7100LC	[24]	94	32	100	*119*	*137*	*4.6*	*4.7*	3/2	5/na/6?	1/na	?/na	5.0	0.8	3	~10		196	0.8
	7200	[24]	94	32	120	~150	~250	*6.4*	*9.1*	3/2	5/na/6?	na/2	na/64	4.4	0.55	3	30		210	1.26
	7300LC	[vi]	96	32	160	~200	~275	*7.8*	*7.6*	3/2	5/na/6?	64/64	2/2		0.5	3	15		259	9
	8000	[33,48]	96	64	180	>400	>600	*11.8*	*20.2*	10/4-	7/9/9	na/na	na/na		0.5	4	>40		345	3.9
	8200	[vi]	97	64	220			15.5	25					3.3	0.5	5				3.8
	8500	[vi]	98	64	360					?/4		1M / 0.5M	4/4		0.25					140
					440			~32	~52											
	8600	[vi]	00	64	560															
	8700	[vi]	01	64																
	8800	[vi]	02?	64																
	8900	[vi]	03?	64																
SH Hitachi	II	[21]	93	16/32	28.7	~8	NA			1/1	5/5/na	4 u.	4	5	0.8	3	0.4		~200	
	7708 (III)	[21]	94	16/32	60	~35	NA			1/1	5/5/na	8 u.	4	3.3	0.5	3	0.6		44	0.8
	7709 (III)	[vi]	97	16/32	80					1/1	5/5/na	8 u.	4	3.3	0.35			0.26		
	7750 (IV)	[vi]	97	16/32	200					2?/2		8/16		1.8	0.25			1.5		

not available yet.

Power: peak power numbers used when available, else estimated from average power. Easier to find peak, rather than average.
Units: Functional units NOT including "system" unit; **Issue**: Peak instructions issued per cycle; **"-"**: Indicates limitations on peak issue rate. **Cache:** On-chip cache (except where footnoted).

SPEC: Numbers that are in *Italics* indicate official CINT95 and CFP95 numbers registered with SPEC (these are peak, not base).

B: Estimated that x60 is 3 times the performance of the x40.

C: Combined total for 2 chips.

D: Data for the RISC-like core. (AMD: rops; NextGen: RISC86 instructions; Intel: uops; IDT: micro-instructions)

E: This was an ECL implementation of the MIPS II ISA..

F: External (in an MCM package)

G: Single-chip CPU / Combined MCM package.

H: These are the highest SPEC numbers reported so far for the 604, which fall below the original estimates (100MHz - 160/165; 133MHz - 200/200)

J: This chip reportedly combines a Pentium and PPC604 on one chip (multiple die?).

L: This P6 has a 256kB L2 (15.5 million xsistors) in the same MCM package (but xsistors not counted in total).

M: This P6 has a 512kB L2 (31 million xsistors) in the same MCM package (but xsistors not counted in total).

N: This P6 has a 1MB L2 (62 million xsistors) in the same MCM package (but xsistors not counted in total).

O: Includes an integrated on-chip graphics co-processor, but is not included in the unit/issue count.

SOURCES (* = Can be found on the CPU Info Center)

[1] = ISSCC92
[2] = ISSCC94
[3] = Hot Chips IV
[4]* = http://netlib2.cs.utk.edu/performance/html/PDStop.html
[5]* = Preliminary Product Sheet for R4200
[6] = to be published.
[7]* = Press Release 4/19/94: 100MHz PPC604
[8] = uP 4/94 (as reported by M. Horowitz)
[9]* = Press Release 3/30/94: 100MHz PPC601
[10] = Spectrum 12/93
[11] = to be published.
[12] = Courtesy M. Horowitz, SPEC Table
[13]* = Product Sheet for R4600
[15] = CompCon 93
[16] = CompCon 94
[17]* = Product sheet for R4400
[18]* = DEC Press Release.
[19] = CY7C601 Data Book
[20] = SPECtable from John Dimarco.
[21] = Hot Chips 94.
[22]* = DEC Press Release 9/7/94
[23]* = John DiMarco's SPEC Table.
[24]* = HP's Online server (http://www.wsg.hp.com/wsg/Strategy/strategy.html)
[25]* = PowerPC WhitePapers (http://www.austin.ibm.com/tech/p2ppc_tech.html)
[27] = from Dave Jaggar, chief architect of the ARM.
[30] = 10/10/94 EE Times
[31]* = Computergram News
[32] = A Guide to RISC Microprocessors. Michael Slater, 1992.
[33]* = from comp.arch (http://infopad/~burd/gpp/announce/pa8000_overview)
[34] = 11/21/94 EE Times
[35] = Leslis Kohn, "Ultrasparc", Invited Speaker, Micro 27 Conf.
[36] = from comp.arch -- Alain Lachapelle (alainl@cam.org)
[37] = uP 12/26/94
[38]* = MIPS Home Page (http://www.mips.com)
[39] = uP 10/24/94
[40] = uP 1/24/94
[41]* = CHIPS and SYSTEMS SPEC Chart, by Gary Snow. (http://infopad.eecs.berkeley.edu/~burd/gpp/summary/snow_survey)
[42]* = CHIPLIST 7.2 by Aad Offerman (http://einstein.et.tudelft.nl/~offerman/chiplist.html)
[43] = ISSCC95
[44] = Motorola PPC Home Page: (http://www.mot.com/PowerPC/prodinfo.html)
[45] = Advanced Microprocessors, Daniel Tabak, 1991
[46] = uP 2/16/94
[47]* = Intel Press Release
[48] = Compcon 95.
[49] = Electronic News 3/20/95
[52]* = Press Release 4/17/95
[53] = uP 6/19/95
[54] = A Practitioner's Guide to RISC Microprocessor Architecture, Patrick Stakem, 1996
[55] = http://www.heise.de/ct/art_ab97/9715spec

[vi] = Vendor Info
[vp]* = Vendor Press Release
[pn]* = PowerPC News
[mw] = MacWeek (online)
[by] = Byte
[bw] = Business Wire
[mr] = Microprocessor Report
[sp] = SPEC
[is##] = ISSCC, where the ## indicates the year.
[cg] = Computergram International
[th]* = Tom's Hardware Guide http://www2.tomshardware.com/irm298.html
[re] = The Register http://www.theregister.co.uk

NOTE: Hobbit & ARM SPEC calculated from 28k Drystones ~= 8 SPECint92

Hobbit = 27k Dry @ 20 MHz
ARM6 = 28k Dry @ 20 MHz