# Complexity Theory

Lecture 1

Anuj Dawar

http://www.cl.cam.ac.uk/teaching/1920/Complexity

### **Texts**

The main texts for the course are:

Computational Complexity. Christos H. Papadimitriou.

*Introduction to the Theory of Computation.*Michael Sipser.

### References

Other useful references include:

Computers and Intractability: A guide to the theory of NP-completeness. Michael R. Garey and David S. Johnson.

P, NP and NP-completeness.

Oded Goldreich.

Computability and Complexity from a Programming Perspective. Neil Jones.

Computational Complexity - A Modern Approach. Sanjeev Arora and Boaz Barak.

### Outline

A rough lecture-by-lecture guide, with relevant sections from the text by Papadimitriou (or Sipser, where marked with an S).

- Algorithms and problems. 1.1–1.3.
- Time and space. 2.1-2.5, 2.7.
- Time Complexity classes. 7.1, S7.2.
- Nondeterminism. 2.7, 9.1, S7.3.
- NP-completeness. 8.1–8.2, 9.2.
- Graph-theoretic problems. 9.3

### Outline - contd.

- Sets, numbers and scheduling. 9.4
- **coNP.** 10.1–10.2.
- Cryptographic complexity. 12.1–12.2.
- Space Complexity 7.1, 7.3, S8.1.
- Hierarchy 7.2, S9.1.
- Descriptive Complexity 5.7, 8.3.

## Algorithms and Problems

Insertion Sort runs in time  $O(n^2)$ , while Merge Sort is an  $O(n \log n)$  algorithm.

The first half of this statement is short for:

If we count the number of steps performed by the Insertion Sort algorithm on an input of size n, taking the largest such number, from among all inputs of that size, then the function of n so defined is eventually bounded by a constant multiple of  $n^2$ .

It makes sense to compare the two algorithms, because they seek to solve the same problem.

But, what is the complexity of the sorting problem?

### Review

The complexity of an algorithm (whether measuring number of steps, or amount of memory) is usually described asymptotically:

#### Definition

For functions  $f: \mathbb{N} \to \mathbb{N}$  and  $g: \mathbb{N} \to \mathbb{N}$ , we say that:

- f = O(g), if there is an  $n_0 \in \mathbb{N}$  and a constant c such that for all  $n > n_0$ ,  $f(n) \le cg(n)$ ;
- $f = \Omega(g)$ , if there is an  $n_0 \in \mathbb{N}$  and a constant c such that for all  $n > n_0$ ,  $f(n) \ge cg(n)$ .
- $f = \theta(g)$  if f = O(g) and  $f = \Omega(g)$ .

Usually, O is used for upper bounds and  $\Omega$  for lower bounds.

## Lower and Upper Bounds

What is the running time complexity of the fastest algorithm that sorts a list?

By the analysis of the Merge Sort algorithm, we know that this is no worse than  $O(n \log n)$ .

The complexity of a particular algorithm establishes an *upper bound* on the complexity of the problem.


To establish a *lower bound*, we need to show that no possible algorithm, including those as yet undreamed of, can do better.

In the case of sorting, we can establish a lower bound of  $\Omega(n \log n)$ , showing that Merge Sort is asymptotically optimal.

Sorting is a rare example where known upper and lower bounds match.

## Lower Bound on Sorting

An algorithm A sorting a list of n distinct numbers  $a_1, \ldots, a_n$ .



To work for all permutations of the input list, the tree must have at least n! leaves and therefore height at least  $\log_2(n!) = \theta(n \log n)$ .

## Travelling Salesman

#### Given

- V a set of nodes.
- $c: V \times V \to \mathbb{N}$  a cost matrix.

Find an ordering  $v_1, \ldots, v_n$  of V for which the total cost:

$$c(v_n, v_1) + \sum_{i=1}^{n-1} c(v_i, v_{i+1})$$

is the smallest possible.

## Complexity of TSP

Obvious algorithm: Try all possible orderings of V and find the one with lowest cost.

The worst case running time is  $\theta(n!)$ .

**Lower bound:** An analysis like that for sorting shows a lower bound of  $\Omega(n \log n)$ .

*Upper bound:* The currently fastest known algorithm has a running time of  $O(n^22^n)$ .

Between these two is the chasm of our ignorance.