\${Unix_Tools}

- exercises

Markus Kuhn

Computer Science Tripos – Part IB

1 The shell

Exercise 1: Write a shell command line that appends: /usr/local/man to the end of the environment variable \$MANPATH.

Exercise 2: Create a new subdirectory and in it five files with unusual filenames that someone unfamiliar with the shell will find difficult to remove. Ask a fellow student to write down for each file the command line that will remove it.

Exercise 3: Given a large set of daily logfiles with date-dependent names of the form log. yyyymmdd, write down the shortest possible command line that concatenates all files from 1 October 1999 to 7 July 2002 into a single file archive in chronological order.

You can fill a directory with 1000 test files using the following make-logs.pl Perl script:

```
#!/usr/bin/perl
use POSIX;
for $i (1..1000) {
    $t=rand 60*60*24*365*45;
    $f=strftime("log.%Y%m%d\n", localtime($t));
    $a=localtime($t);
    `echo "$a" >$f`;
}
```

Exercise 4: Write down the command line that appends the current date and time (in Universal Time) and the Internet name of the current host to the logfile for the respective current day (local time), using the above logfile naming convention.

Exercise 5: What outputs will be the result of typing in the following shell command lines (in that order)? Explain why.

```
$ a=1
$ a=2 echo $a ; echo $a
$ a=3 ; echo $a ; echo $a
$ ( a=4 ; echo $a ) ; echo $a
$ { a=5 ; echo $a ; } ; echo $a
$ a=6 bash -c 'echo $a'
$ a=7 ; bash -c 'echo $a'
$ bash -c "echo $a"
$ export a
$ bash -c 'echo $a'
```

Exercise 6: Explain what happens if the command "rm *" is executed in a subdirectory that contains a file named "-i".

Exercise 7: Write a shell script "start_terminal" that starts a new "xterm" process and appends its process ID to the file ~/.terminal.pids. If the environment variable \$TERMINAL has a value, then its content shall name the command to be started instead of "xterm".

Exercise 8: Write a further shell script "kill_terminals" that sends a SIGINT signal to all the processes listed in the file generated in the previous exercise (if it exists) and removes it afterwards.

2 Text tools

Exercise 9: Write down the command line of the single sed invocation that performs the same action as the pipe

head -n 12 <input | tail -n 7 | grep 'with'

3 File and network tools

4 Revision control

Exercise 10: Generate a Subversion repository and place all your exercise solution files created so far into it. Then modify a file, commit the change, and create a patch file that contains the modification you made. And finally, retrieve the original version of the modified file again out of the repository.

5 Build tools

<u>Exercise 11:</u> Add a Makefile with a target solutions.tar.gz that packs up all your solutions files into a compressed archive file. Ensure that calling make solutions.tar.gz will recreate the compressed package only after you have actually modified one of the files in the package.

Exercise 12: Write a C program that divides a variable by zero and execute it. Use gdb to determine from the resulting core file the line number in which the division occurred and the value of the variable involved.

6 Perl

Exercise 13: When editing sentences, users of text editors occasionally leave some word duplicated by by accident. Write a Perl script that reads plain text files and outputs all their lines that contain the same word twice in a row. Extend your program to detect also the cases where the two occurrences of the same word are separated by a line feed.